

# **TIBCO General Interface™**

## **Release Notes**

*Software Release 3.3.0  
February 2007*

## **Important Information**

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN TIBCO GENERAL INTERFACE INSTALLATION). USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document contains confidential information that is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIB, TIBCO, TIBCO Adapter, Predictive Business, Information Bus, The Power of Now, TIBCO General Interface, TIBCO General Interface Framework, and TIBCO General Interface Builder are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

THIS SOFTWARE MAY BE AVAILABLE ON MULTIPLE OPERATING SYSTEMS. HOWEVER, NOT ALL OPERATING SYSTEM PLATFORMS FOR A SPECIFIC SOFTWARE VERSION ARE RELEASED AT THE SAME TIME. PLEASE SEE THE README.TXT FILE FOR THE AVAILABILITY OF THIS SOFTWARE VERSION ON A SPECIFIC OPERATING SYSTEM PLATFORM.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

Copyright © 2001-2007 TIBCO Software Inc. ALL RIGHTS RESERVED.

TIBCO Software Inc. Confidential Information

# Contents

|   |          |
|---|----------|
| <b>Release Notes</b> .....                        | <b>1</b> |
| New Features .....                                | 2        |
| Release 3.3.0 .....                               | 2        |
| Release 3.2.0 .....                               | 3        |
| Release 3.1.1 .....                               | 15       |
| Release 3.1.0 .....                               | 15       |
| Changes in Functionality .....                    | 23       |
| Release 3.3.0 .....                               | 23       |
| Release 3.2.0 .....                               | 23       |
| Release 3.1.0 .....                               | 24       |
| Deprecated Features .....                         | 25       |
| Release 3.2.0 .....                               | 25       |
| Release 3.1.0 .....                               | 25       |
| Migration and Compatibility .....                 | 27       |
| Closed Issues .....                               | 28       |
| Known Issues .....                                | 39       |
| Mac and Firefox Known Issues .....                | 39       |
| Browser Limitations and the Margin Property ..... | 40       |
| General Known Issues .....                        | 41       |



# Release Notes

Check the TIBCO Developer Network web site at <http://developer.tibco.com> for product information that was not available at release time.

## Topics

---

- *New Features, page 2*
- *Changes in Functionality, page 23*
- *Deprecated Features, page 25*
- *Migration and Compatibility, page 27*
- *Closed Issues, page 28*
- *Known Issues, page 39*

## New Features

---

This section lists features added since the last major (3.0) release of this product.

### Release 3.3.0

This release introduces the following updates:

#### Web Browsers

##### Browsers for Deployment

TIBCO General Interface applications and TIBCO General Interface™ Framework can be deployed to the following browsers:

- Internet Explorer 7.0 and 6.0.x for Windows
- Firefox 2.0 and 1.5.x for Windows, Linux, and Mac OS X

##### Browsers for TIBCO General Interface™ Builder

TIBCO General Interface Builder runs in the following browsers:

- Internet Explorer 7.0 and 6.0.x for Windows
- Firefox 2.0 and 1.5.x for Windows

#### TIBCO General Interface Documentation

The following documents now form the TIBCO General Interface documentation set:

- *TIBCO General Interface Installation* Read this manual for General Interface installation instructions.
- *TIBCO General Interface Getting Started* Read this manual for overview information and a tutorial that explains how to build a TIBCO General Interface application.
- *TIBCO General Interface Developer Guide* Refer to this manual for in-depth information about developing and deploying TIBCO General Interface applications.
- *TIBCO General Interface Component Guide* Refer to this manual to learn more about components and the Charting add-in, as well as component properties and events.

- *TIBCO General Interface API Reference* Refer to this online help content for descriptions of the TIBCO General Interface JavaScript API functions and methods.
- *TIBCO General Interface Migration* Read this manual for instructions on migrating applications from previous General Interface releases.
- *TIBCO General Interface Release Notes* Read the release notes for a list of new and changed features. This document also contains lists of known issues and closed issues for this release.

To open the documentation in TIBCO General Interface Builder, choose **Help > Help Contents**. Documentation is also available online at <http://developer.tibco.com>.

## Release 3.2.0

This release introduces the following new features and updates:

- TIBCO Developer Network on page 3
- Web Browsers on page 4
- General Enhancements on page 6
- XML Mapping Utility on page 6
- Application Deployment on page 8
- Development Productivity on page 9
- General Interface Framework on page 11
- API Changes on page 12
- GUI Components on page 13
- Localization on page 14
- Samples on page 14
- Documentation on page 15

### TIBCO Developer Network

The TIBCO Developer Network has moved to a new location. Visit <http://developer.tibco.com> for General Interface™ forums, sample applications, videos, and much more.

## Web Browsers

### Browsers for Deployment

TIBCO General Interface applications and TIBCO General Interface Framework can be deployed to the following browsers:

- Internet Explorer 6.0.x for Windows
- Firefox 1.5.x for Windows, Linux, and Mac OS X

### Browsers for TIBCO General Interface Builder

TIBCO General Interface Builder runs in the following browsers:

- Internet Explorer 6.0.x for Windows
- Firefox 1.5.x for Windows

### Browser Limitations

Some limitations in web browsers could restrict the kinds of applications which can be deployed. For known issues with browsers, see Known Issues on page 39.

### General Interface API

Methods that are implementable only in specific browsers are specified in the TIBCO General Interface API documentation. Search for Firefox and Internet Explorer in the API documentation.

### **Charting Add-in**

The Charting add-in is supported on the following browsers and platforms in XHTML and HTML pages:

- Internet Explorer 6.0.x (VML) on Windows
- Firefox 1.5.x (SVG) on Mac OS X, Linux, and Windows

For supported platform versions, see `readme.txt` in the `GL_HOME` directory.

## General Enhancements

General enhancements include the following:

- Improvements to the `jsx3.gui.Select` class include:
  - Support for `@jsxstyle` and `@jsximg` CDF attributes
    - Use `@jsxstyle` to apply a CSS style to a record. Specify any CSS code. For example, `jsxstyle="font-weight:bold;"`.
    - Use `@jsximg` to reference a graphic file to use as an icon. Specify the file path relative to the project directory, for example, `images/icon.gif`. Image position depends on the component. For best results, use a 16x16 transparent GIF file.
  - Vetoable Before Select model event
- Menu hot key accelerators follow user interface guidelines for Mac OS X and Windows.
- Support for the Command key on Mac OS X has been added. Actions that require Ctrl+click on Windows translate to Command+click on Mac OS X (Ctrl+click is equivalent to right-click on Mac).
- When General Interface™ Builder opens XSL and XML files for editing, it honors their encoding.

## XML Mapping Utility

The XML Mapping Utility includes these enhancements:

- Re-parse part of the rules tree. To recreate deleted nodes, right-click a node in the Rules Tree and choose Reparse to re-parse from that node down.
- Ability to choose a specific prototype for DOM projection.
- Log messages in the Mapper Log are color coded. For example, errors are red, traces are gray, and so on.
- JavaScript code generated by the XML Mapping Utility has changed due to a signature change in the `jsx3.net.Service` class. Rules files IDs are now passed as an argument instead of URLs. See General Interface Framework on page 11.

## WSDL File Browsing

The XML Mapping Utility now resolves paths to WSDLs relative to the project. It's recommended that you copy WSDLs to a `wSDL` directory in your project. Then enter `wSDL/wSDL_file.xml` in the URL field of the XML Mapping Utility.

However, if you need to resolve a path to a WSDL outside of your project, use an absolute resolver, such as `jsxuser:///` and `jsxapp:///`.

- **jsxuser:///...** Resolves relative to the parent of the JSXAPPS directory, which is the workspace. When General Interface Builder is running, this URI resolves relative to the workspace directory.
- **jsxapp://app/...** If the Server instance corresponding to the host portion of the URI is loaded into memory, the URI is resolved relative to the application base directory (`jsxappbase`).

### jsx3.net.Service

The following enhancements have been made to the `jsx3.net.Service` class. For more information, see the API documentation.

- Added a new `compile()` method that allows the output mapping rules (those that handle the server's response) to be compiled into an equivalent XSLT document, which increases performance. This allows the `Service` class to use the native XSLT processor as opposed to JavaScript in order to convert the server's response to CDF. The Sample performance difference to convert 400 records from SOAP to CDF is as follows: Firefox: 0.09 seconds vs 4.0 seconds and Internet Explorer: 0.13 seconds vs 10.1 seconds.
- Updated the `doCall()` method to accept a parameter, allowing the developer to cancel the send if the outgoing message did not pass the validation rules.
- Updated the `jsx3.net.Service.setInboundURL()` and `jsx3.net.Service.setOutboundStubURL()` methods to support paths that are relative to the project directory.

For example, if the project directory for the context server is `test`, then the following valid inputs are equivalent:

- `xml/typical.xml`
- `jsxapp://test/xml/typical.xml`
- `JSXAPPS/test/xml/typical.xml`

- Added additional debug statements for more detailed debugging capabilities when running in trace mode. Error handling has also been expanded. Added a new event type that is published each time a rule in the rules file is executed, providing even greater control over how each node in a message is created or processed.

## Application Deployment

The following deployment enhancements have been added:

- Accelerated load time
  - Class loading improvements
 

Payload size is reduced as applications now dynamically load ("lazy loading") only those classes which are needed. Classes now fall into three categories. (1) Required classes are always loaded. (2) Optional classes introduced in General Interface 3.2 classes are dynamically loaded. For example, `jsx3.gui.ColorPicker`. (3) Optional classes introduced prior to General Interface 3.2 are dynamically loaded only if the `jsx1t` deployment parameter is set to `true` in the web page that launches the application. This improves backwards compatibility. See Deployment Parameters in the Deploying Applications chapter of *TIBCO General Interface Migration*.

Use the `jsx3.require()` method to explicitly load classes synchronously. For example, debugger classes are now dynamically loaded and need to be called using the `require()` method. See Debugging on page 23.

```
jsx3.require("jsx3.ide.Debugger");
```

Specify the classpath to your classes on the Classpath page of the Project Settings dialog (Project > Project Settings).
  - Changes to how add-ins are loaded improve the load time for TIBCO General Interface Builder and General Interface applications. See Add-ins on page 24.
- Simplified portal deployment
  - Separation of `GL_HOME` from the workspace allows for easier application deployment. Choose your own workspace or use the default. Modify the workspace directory in the Workspace field on the Paths page of the IDE Settings dialog (Tools > IDE Settings).
  - Application resources are specified using relative paths, which allows for easier portability of code from one project to another and simplifies the relocating of applications in the `JXSAPPS` folder hierarchy.
  - Applications can be loaded multiple times on a single portlet page with the `jsxappns` (namespace) deployment parameter that overrides the namespace in the configuration files. See Deployment Parameters in *TIBCO General Interface Migration*.
- A loading progress indicator now displays when the General Interface Framework loads. For multiple applications loading in the same page, only one indicator shows the loading of the General Interface™ Framework, which

is shared by all portlet applications. Subordinate progress indicators show the loading of each portlet application.

To specify the type of progress indicator displayed, add the `jsxapploader` deployment parameter to the HTML `script` element on the web page that launches the application(s). For example, setting `jsxapploader=1`, is a good choice for portlets, because this would load a subordinate progress indicator. See Deployment Parameters in *TIBCO General Interface Migration*.

## Development Productivity

TIBCO General Interface Builder includes the following productivity enhancements:

- The Common Interface Format (CIF) can be used to create GUI definition files on-the-fly or manually. The CIF format provides improved readability and smaller file size. TIBCO General Interface transforms these files to the current GUI XML structure for rendering. Currently, General Interface Builder can read but **not** save CIF files. Any edits made to a CIF file are saved in the standard serialization format. See Custom TIBCO General Interface Formats in *TIBCO General Interface Migration*.
- The XML/XSL Merge Tool supports opening multiple instances of the tool.
- Reorganization of options and preferences.
  - The Deployment Options dialog has been renamed to Project Settings dialog (Project > Project Settings). Project settings include deployment, add-ins, class path settings, and legacy settings.
  - The Preferences dialog has been renamed to IDE Settings (Tools > IDE Settings). Settings include IDE settings, hot keys, and user home.
- Writing and debugging code
  - The `logger.xml` file has been moved to the root of `GI_HOME` and now supports a configurable location. Use the environment variable, `jsx_logger_config`, in the `script` element of the launch page to specify

its location. See Logging and the Application Monitor in *TIBCO General Interface Migration*.

- Color coding of messages in the System Log palette, Application Monitor, and the Mapper Log in the XML Mapping Utility. For example, error messages are displayed in red and traces in gray.
- A configurable, optional sound can be triggered when messages are printed to the System Log palette. To enable sound for messages, change the `beepLevel` property in `GL_HOME\logger.xml` from `jsx3.util.Logger.OFF` to a message logging level, such as `jsx3.util.Logger.ERROR`. Sound is played for the specified logging level and higher. Firefox requires a plug-in that can play .wav files.
- JavaScript type-ahead lists (Ctrl+spacebar) are available in any code window and text areas with blue grid backgrounds. Type-ahead lists display the General Interface APIs and allow you to automatically insert package names, class names, methods, and fields.
- Component Hierarchy features: (1) Right-click a component and choose **Copy Name to Clipboard** to get the object name. (2) Right-click a component and choose **Copy Getter Code to Clipboard** to copy code for getting a handle to the object (`getJSXByName`).
- General Interface Builder now traps the Tab key in main stage code editors as 4 spaces. This is a General Interface Builder feature and does not affect runtime.
- When restoring a child component from the Recycle Bin, if the parent is gone, the child is restored to <ROOT>.
- General Interface Builder has been rearchitected for improved load performance.
- General Interface Builder keyboard shortcuts can be configured in the IDE Settings dialog (Tools > IDE Settings > IDE Hot Keys).
- Running General Interface Builder and projects
  - Ability to launch General Interface Builder in XHTML or HTML mode. Choose `GI_Builder.xhtml` or `GI_Builder.html` from `GL_HOME`. Running

in XHTML mode is useful for developing and testing applications that run in XHTML pages, such as portlet applications.

- When General Interface Builder is run in XHTML mode, an error message is output when the Text/Html property contains non-compliant code.
- Choosing Project > Run Project, runs the project in the same mode as TIBCO General Interface Builder. For example, if General Interface Builder is running in XHTML mode, the project also runs in XHTML mode.
- Run your project from a local HTTP server. Choose **Project > Run Project from HTTP**. The deployed project relative path must match the local drive relative path to shell.html for this run option to work.
- Run Project warning displays if any open tabs have unsaved changes. A dialog displays a warning that some files are not saved and allows you to Run Without Saving, Cancel, or Save and Run.

## General Interface Framework

TIBCO General Interface Framework includes the following changes:

- The `persistAll` argument has been added to the `toXML()` method of the `jsx3.app.Model` class, which causes the returned serialized form to include DOM nodes with transient persistence. This is useful when you want to save the exact state of the application for troubleshooting purposes.
- Rules file IDs are now passed as an argument to `jsx3.net.Service` instead of URLs. If rules files are moved to new locations, there's no need to update the URL, because the ID is used instead. The `objService` variable generated by the XML Mapping Utility has a signature change and now accepts three arguments: server, resource ID, and operation name. The new syntax is:
 

```
var objService = ServerName.loadResource(Project_Resource_File_Id);
objService.setOperation(Operation Name);
```
- The new Matrix component provides an `insertBefore()` method and a visual control for dragging and dropping multiple records to a new location.
- Instantiate CDFs directly without using a GUI control with the new `jsx3.xml.CDF.Document` class. See API Changes on page 12.
- User-defined XSL properties, `jsx1` through `jsx10`, have been added to `jsx3.gui.Matrix`.
- Performance improvements to the `Array.join()` method instead of String concatenation for the `String.fromBase64()` and `String.toBase64()`.
- The `Form` class provides an API that allows you to see the hidden iframe where the HTML for the form post is being built and where the response comes back from the server.

## API Changes

The following changes have been made to the TIBCO General Interface API. Search for "3.2" in *TIBCO General Interface API Reference* in the online help.

- `jsx3.app`
  - `jsx3.app.AddIn` A class that represents a JSX add-in. The JSX system creates an instance of this class for every add-in that is loaded.
  - `jsx3.app.Properties` Represents a repository of dynamic properties. Dynamic properties are simply name-value pairs. Dynamic properties can be loaded from an XML file in the CDF dynamic property format.
- `jsx3.gui`
  - `ColorPicker` A GUI class that allows the user to pick a color using an HSB (hue-saturation-brightness) picker. See `jsx3.gui.ColorPicker` in the API documentation.
  - `HotKey` Encapsulates a keydown event listener that is invoked by a certain combination of keys pressed simultaneously.
  - `Image` Renders an image. See `jsx3.gui.Image` in the API documentation.
  - `Matrix` and `Matrix.Column` See Matrix Components on page 13.
  - `TimePicker` See Time Picker Component on page 13.
  - `Window` Allows for rendering a branch of the DOM of an application in a separate browser window. This is similar to the implementation of the TIBCO General Interface Builder API documentation window.
- `jsx3.net.Service` See `jsx3.net.Service` on page 7.
- `jsx3.net.URIResolver` interface An interface specifying the methods necessary to define a context against which URIs are resolved.
- `jsx3.util`
  - `DateFormat` Formats and parses dates according to a token-based string format. This class is fully localized.
  - `Locale` Represents a region of the world. Other classes may be localized, meaning that their behavior depends on their assigned locale.
  - `MessageFormat` Constructs localized messages from a pattern and parameters. A message format takes a list of arguments, formats them, and inserts them into the pattern at specific places.
  - `NumberFormat` Formats and parses numbers.
- `jsx3.xml.CDF.Document` A subclass of `jsx3.xml.Document` that implements the CDF interface. This class exposes the CDF convenience

methods on an XML document and allows you to work directly with a CDF document, without needing to work with a GUI list control. Use this class for adding records and so on.

- `jsx3.xml.Cacheable` XML Transformers replace XSL ID, XSL URL, and XSL String:
  - `getXMLTransformers()`
  - `setXMLTransformers()`

## GUI Components

The classes, `jsx3.gui.Grid`, `jsx3.gui.Column`, and `jsx3.gui.List`, have been deprecated and are not supported in Firefox. The new Matrix classes, `jsx3.gui.Matrix` and `jsx3.gui.Matrix.Column`, have replaced the deprecated classes. New Matrix prototypes are available in the Component Libraries palette. See [Deprecated APIs](#) on page 25.

### Tree Component

The Tree prototype has been moved to the Miscellaneous folder of the Component Libraries palette.

### Matrix Components

New Matrix components, which are composites of the List, Grid, and Tree components, provide richer functionality. Matrix is fully supported in Firefox and Internet Explorer. It's recommended that you use Matrix instead of Grid, Column, and List as they have been deprecated.

These components support such features as dynamic loading of lists for better performance, tree rendering of 100 levels deep, hierarchical lists that behave like trees, multi-column trees that behave like lists, and many other features. For more information, see `jsx3.gui.Matrix` and `jsx3.gui.Matrix.Column` in *TIBCO General Interface API Reference* and *Using Matrix Components in TIBCO General Interface Migration*.

### Time Picker Component

The new TimePicker component, `jsx3.gui.TimePicker`, is a clock for selecting the hour, minute, and AM or PM. Seconds, milliseconds, and a 24 hour clock can also be displayed. This control is localized.

## New GUI Controls and Behaviors

- Color Picker allows the user to pick a color using an HSB (hue-saturation-brightness) picker.
- Date and Time Picker support keyboard navigation into and out of controls, as well as within the controls.
- Date Picker permits typing of date value into the DatePicker box as an alternative entry method.
- Paint methods are now XHTML compliant.
- Drop-downs for combos and selects can be wider than the unexpanded control.
- Insert stack and tab children in a specific location. See these methods of the `jsx3.app.Model` class in the API documentation: `insertBefore()`, `getFirstChild()`, `getLastChild()`, `getNextSibling()`, and `getPreviousSibling()`.
- Combo now has a `maxLength` property and method.

## Localization

This release includes several new localization features:

- Date, time and number formats are now externalized in the `MessageFormat`, `NumberFormat` and `DateFormat` classes. For more information, see the new `jsx3.util` API classes for localization in General Interface Framework on page 11.
- A new deployment option, `Default Locale`, for setting language and country codes for localizing applications.

## Samples

Product samples have been updated to the current version. These include `Chart`, `WSDL_Mapping_1`, and `WSDL_Mapping_2`.



Choosing an existing workspace doesn't replace previous sample applications with updated 3.2 sample applications. This built-in functionality is designed to prevent workspace files from getting overwritten. Create a new workspace to get the updated sample applications.

More samples are available at the TIBCO Developer Network at <http://developer.tibco.com>.

## Documentation

This release includes the following changes to documentation:

- *TIBCO General Interface Builder GUI Reference* has been updated and included in this release.
- *TIBCO General Interface Builder Chart User's Guide*:
  - Chapter 1, *Working with Charts*, has been moved to *TIBCO General Interface Builder Getting Started Guide*.
  - Chapter 2, *Chart Components*, has been moved to *TIBCO General Interface Builder GUI Reference*.
  - *TIBCO General Interface Builder Chart User's Guide* has been removed.
- Class property descriptions have been added to the Properties Editor palette. Hover over a property, such as *Padding*, to see a description of it in the spyglass.

## Release 3.1.1

This release introduces the following enhancements:

- The XML Mapping Utility's *Generate Code* button is now a menu button, which introspects for the available operations. If the rule file has not been saved, selecting an operation triggers an alert which says to save the file. Only when the rule file has been saved does the code generator put the code on the clipboard and alert the user to paste the code to the desired location.
- The signature for the `Model.loadXML()` method now accepts `jsx3.xml.Document` as well as `string`. Without this method the developer cannot pre-cache GUI components in the cache to avoid run-time reloading.

## Release 3.1.0

This release introduces a wide variety of new features in the following categories:

- XML Mapping Utility on page 16
- Package Reorganization on page 16
- Usability Enhancements on page 18
- Logging on page 19
- Event Model on page 19
- GUI Components on page 20
- Help on page 22

## XML Mapping Utility

- Expanded support, including:
  - WSDL (Document-Literal and RPC-Encoded)
  - Schema (2001)
  - XML/XHTML (including RSS, REST, and so on)
- Step-through tester with detailed logging, describing each node as it is processed by the XML Mapping Utility.
- Automatic UI projection. Fields described in a WSDL (or any other source format) can be leveraged by the XML Mapping Utility to create the auto-generate the GUI.
- Improved logging support with detailed information about why a mapping may have failed, including unsupported schema nodes, malformed XML, improper imports, and so on.
- Support for offline testing and configuration, allowing the mappings to be built and tested without accessing the live services.
- Automatic migration of 3.0 maps to the new 3.1 format.
- Test message generator, capable of simulating the live service.

See the *TIBCO General Interface Builder Getting Started Guide* for information on many of these features.

## Package Reorganization

**jsx3** The `jsx3` package contains the deprecated classes from General Interface™ 3.0. Most of these classes have been moved into one of the following packages: `app`, `gui`, `net`, `util`, and `xml`. These classes can still be referred to by their old names; however this is deprecated and not guaranteed to work in future versions.

**jsx3.app** The `jsx3.app` package contains classes related to General Interface applications. Classes in this package are used extensively in application JavaScript code.

The `Server` class is the controller in the JSX architecture. An instance of this class is created by the JSX runtime for each loaded application. `Server` provides access to the application DOM (`getRootBlock()`, `getDOM()`, `getJSX()`, and so on), the application cache (`getCache()`), and application settings (`getSettings()`).

The `Monitor` class, new in 3.1, is a vital tool in debugging running applications. It brings the power of the TIBCO General Interface Builder system log to running applications by displaying logging messages in a separate browser window.

**jsx3.chart** The `jsx3.chart` package contains all the classes contained in the General Interface Charting add-in. This package provides a collection of GUI controls that render charts. Bar, column, area, line, plot, bubble, pie, and doughnut charts are supported.

The General Interface Charting add-in provides the following features:

- Prototype charts effortlessly in TIBCO General Interface Builder, just like any other GUI control
- Render from any standard CDF data source as a chart
- A rich event model for implementing interactive charts
- Offload chart rendering to the client browser, no plug-in required

**jsx3.gui** The `jsx3.gui` package contains all the GUI controls available by default in the JSX runtime. Classes in this package are typically not instantiated by the developer. Rather they are prototyped in TIBCO General Interface Builder, serialized to component files, and deserialized at application runtime by the JSX runtime. TIBCO General Interface Builder provides at least one prototype for each class in this package.

General Interface 3.1 contains the following new GUI controls:

- `ImageButton` A simple button class comprised of a separate image file for each state of the button.
- `Slider` A form control comprised of a track and a handler that is draggable along the track.
- `Sound` Provides a standard interface for playing sounds of different formats.

**jsx3.lang** The `jsx3.lang` package contains the classes that comprise the General Interface class, inheritance, and introspection model. This model, introduced in General Interface 3.1, extends JavaScript 1.5 with the following features:

- A simple syntax for declaring classes, with support for “extends” and “implements”
- Mixin interfaces
- An extended base class, `jsx3.lang.Object`, from which all other classes descend
- Fully introspectable classes, interfaces, packages, and methods
- A base exception class, `jsx3.lang.Exception`, with stack tracing facilities
- Access to the overridden method determined by context, with the `jsxsuper()` and `jsxsupermix()` methods

Developers who use this package, rather than the typical facilities provided by JavaScript 1.5 to define custom classes will tap the significant developer-friendly features provided by this package.

**jsx3.net** The `jsx3.net` package contains various classes related to HTTP communication. Applications that use the data mapper and/or communicate with web services or legacy HTTP forms will use the classes in this package extensively.

`Form` allows a General Interface application to submit to legacy HTTP forms by either GET or POST and allows for file upload to such forms. `Request` is a platform independent wrapper of the browser XMLHTTP control. It allows any XML data source to be fetched either synchronously or asynchronously. `Service` is the programmatic interface onto the data mapping utility. `URI` is a simple utility class that is useful for parsing and resolving URIs.

**jsx3.util** The `jsx3.util` package contains various utility classes.

`EventDispatcher` is a mixin interface that when implemented by a class provides functionality according to the publish-subscribe design pattern. The `Logger` class, new in General Interface 3.1, is the primary interface of the General Interface logging system.

**jsx3.xml** The `jsx3.xml` package contains various classes related to XML processing.

The `Document`, `Entity`, and `Processor` classes provide platform independent interfaces onto the native browser XML DOM and XSLT libraries. `CDF` is a mixin interface, implemented by all CDF GUI controls, that provides an object-oriented interface onto the CDF XML format. `Cacheable`, also implemented by many GUI controls, is a mixin interface that provides functionality related to fetching and storing XML and XSL documents in the application cache.

## Usability Enhancements

- TIBCO General Interface Builder can now be launched using `GI_Builder.hta` file in `GI_HOME`. When launched using this file, the browser menus and browser toolbars are hidden, leaving maximum screen area for development tasks.
- Tree components now support selecting multiple nodes. A new Multi-Select property for enabling or disabling this feature was added. When the property is set to Multi-Select, users can press the Ctrl+click to select multiple nodes in the hierarchy.

This change also allows you to select multiple items in the Local Data Cache palette and Project Files palette in TIBCO General Interface Builder, as well as the Rules Tree in the XML Mapping Utility.

- **Palette features** The XSL Parameters and Attributes Editor palettes are now hidden by default. You can display these palettes by manually selecting them in the Palettes menu.

The state and position of floating palettes is now stored as a project setting in TIBCO General Interface Builder, and preserved across project sessions. If a palette is floating when a project is closed, when the project is reopened the palette is still floating in the same position.

## Projects

- TIBCO General Interface Builder projects can now be located in subfolders. In the Create New Project dialog, specify the project name as *project\_path/project\_name*, where *project\_path* is one or more directory names under the *GI\_HOME/JSXAPPS* directory. Separate directory names with forward slash characters (/).
- A new option for specifying whether TIBCO General Interface Builder automatically opens the last project on startup was added to Tools menu.
- Project files that begin with the string `jsx` are now supported in TIBCO General Interface Builder.
- A new Watermark field for moving the Powered By TIBCO text string to the left, center, or right side of your application window was added to the Project Deployment Options dialog.

## Logging

This release contains a new logging system defined in the `jsx3.util.Logger` class and a new `jsx3.app.Monitor` class for displaying logging messages in a separate browser window. For details, see the online API help in TIBCO General Interface Builder.

For more information and code samples, check the TIBCO General Interface Developer Community at <http://developer.tibco.com>. See the document *Advanced Logging*.

## Event Model

This release introduces significant changes to the way that application components handle events. The global event object (`jsx3.EVENT`) is deprecated. For API calls and user interactions that interact with events, the new model requires explicitly passing the event object, an instance of `jsx3.gui.Event`. For more information and code samples, check the TIBCO General Interface Developer Community at <http://developer.tibco.com>. See the document *Model Events*.

These changes are implemented in a backward-compatible manner, so that immediate migration is not necessary. Existing projects and applications run seamlessly without modification. However, new projects use the new event protocol unless the Event Protocol field is set to 3.0 in the Deployment Options dialog.

## GUI Components

- `TextBox` and `Password` prototype components have a new `Max Length` property for specifying the maximum number of characters a user can type in a text box or password field.
- `Select` and `Combo` components support for the XSL attribute `jsxshallowfrom` for specifying a portion of a CDF structure to render in the component. Previously, any hierarchy information in CDF data was not shown by these components. You can add this parameter using the XSL Parameters palette, which can be accessed using the Palettes menu. To display only CDF records that are children of the root element, specify `jsxroot`.
- `Tree` components support a new `jsxdeepfrom` XSL parameter for specifying the `jsxid` value of the first visible node in the tree. All descendants of this node are also displayed, while the root node remains hidden.
- Support for the `insertHTML` method was added to the `jsx3.gui.Stack` and `jsx3.gui.StackGroup` classes for more efficient painting.
- `Select` and `Combo` components now support the `jsxtip` system attribute in the CDF document. This attribute provides tooltip text when the user hovers the mouse cursor over the component.
- The `Block` and `BlockX` components now support a double-click event, which allows images and labels to be used as buttons. The `setTip()` method was also enhanced to automatically repaint tooltip text. For information on descendant components, see the description of `jsx3.gui.Block` in the online API help.
- A new class, `jsx3.gui.ImageButton`, was added with support for image rollover, and for relevant events. A different image can be used for each button state. For details, see the class description in the online API help.
- Other new API classes in this release include `jsx3.util.Sound` and `jsx3.gui.Event`.
- **List and Grid components** The `List` and `Grid` prototype components have been enhanced as follows:
  - **New events** The `Before Sort` and `After Sort` events fire just before or after a user sorts the contents of a `List` or `Grid` component. `Before Sort` also allows the index value of the clicked column to be modified before the data is

sorted. After Sort can be used to perform cleanup tasks after data is repainted.

Similarly, the Before Resize and After Resize events fire when a user resizes the component. Resizing a component with many data rows can be canceled, or on-screen dimensions can be modified to optimize the display.

- **Attributes for XSL parameters** Support for 4 new XSL attributes was added. You can add these parameters using the XSL Parameters palette, which can be accessed using the Palettes menu.

`jsxshallowfrom` allows you to specify a portion of a CDF structure for rendering in non-hierarchical GUI components, such as List and Grid. Previously, any hierarchy information in CDF data was not shown by these components. Specify the name of the immediate parent element for this attribute. To display only CDF records that are children of the root element, specify `jsxroot`.

`jsxbg1` allows you to specify the background color of odd-numbered rows, beginning with the first row. `jsxbg2` allows you to specify the background color of even-numbered rows, beginning with the second row.

`jsxstyle` allows you to specify any valid CSS style for a record. Only the record that includes this attribute uses the specified style.

- **Additional checkbox state** CheckBox components can be selected, unselected, or partially selected. The new partially selected state can be programmatically set, for example to select a parent object in a nested list when a child object is explicitly selected. To indicate the partial selection state, the checkbox displays a minus sign (-) character.
- **Select and Combo components** The tab and arrow keys can now be used to navigate in the list of values and select a value. The type-ahead feature can be used for narrowing the list of values in a Combo component, provided the `jsxid` and `jsxtext` attributes have identical values in the CDF file used by the component.
- **Slider component** A new class, `jsx3.gui.Slider` and a new prototype component, Slider (H) were added. Use a slider to allow users to set a numerical value in a defined range. Clicking in the slider bar moves the handle to the clicked location. Dragging the handle changes the slider value.
- **API methods for masking** The `showMask` and `hideMask` methods were added to the `jsx3.gui.Block` class. These methods can be used to hide or disable any area of the screen. An optional message can be displayed.

## Help

- A link to information on writing regular expressions was added to the Help menu in TIBCO General Interface Builder. To access this web page, select **Help > Internet Resources > Regular Expressions Guide**.
- **API reference**
  - Better visibility of JavaScript native functions, navigable type links, and automatic search cancellation when the window is closed during a search operation.
  - A menu in the API help window was added with a existing option, Show Inherited Members, and a new option, Show Deprecated Classes and Members.
  - An HTML version, displaying in a separate browser window, is now available.

## Changes in Functionality

---

This section discusses changes in functionality since the last major (3.1.0) release of this product.

### Release 3.3.0

In some versions of Internet Explorer 6 and 7, XML, XSL, and component serialization files may not always be refetched from an HTTP/S server even if they have changed on the server.

For more information on Internet Explorer caching and best practices, see "Understanding Internet Explorer Caching" at <http://developer.tibco.com> in the Tips and Techniques section.

### Release 3.2.0

Every effort has been made to provide backward compatibility from General Interface 3.2 to 3.1. However, some migration steps are required. For migration instructions, see *TIBCO General Interface Migration*.

### TIBCO General Interface Framework

- For more flexibility in project deployment, the following changes have been made:
  - Projects are now saved to a workspace directory. The *workspace* is the directory that contains your projects, custom add-ins, custom prototypes, and your user settings for General Interface Builder. You can create a new workspace, choose an existing directory, or use the default directory. To change the workspace, choose **Tools > IDE Settings > Paths** and specify the path in the Workspace field.
  - The launch page and JSXAPPS and JSX folders can each be in any location on the server.

See Application Deployment on page 8.

- Debugging
  - Debugger classes are now dynamically loaded. You must use the `jsx3.require()` method before any `jsx3.ide.debug()` statements to load debugger classes. For example,

```
jsx3.require("jsx3.ide.Debugger");
```

- Add-ins

To accelerate TIBCO General Interface Builder and GI application load time, add-ins are only loaded when required.

— By default, add-ins, such as Charting, are no longer loaded automatically. Add-ins must be enabled in the project to have access to those features. To enable add-ins, choose **Project > Project Settings > Add-ins**. Select the add-in, Save, and restart TIBCO General Interface Builder.

— The Mapping add-in is always available and doesn't need to be enabled in the Project Settings dialog.

— An addin directory has been added to the workspace for storing any custom add-ins you create. These add-ins aren't loaded unless enabled in the project.

- How some properties are specified has changed. Left, Top, Width, and Height properties can be specified in implied pixels or in percentages. Padding, Margin, and Border properties have also been updated. Use the abbreviated TIBCO General Interface syntax for better performance or use the CSS2 syntax. See *Entering CSS Values in TIBCO General Interface Migration*.

## TIBCO General Interface Builder

The Deployment Options dialog and the Preferences dialog have been renamed and some new options added. See *Reorganization of options and preferences*, on page 9.

## Release 3.1.0

Every effort has been made to provide backward compatibility from General Interface 3.1 to 3.0. In most cases applications will work with no changes. For more information on migrating 3.0 projects to 3.1, see *Migrating 3.0 Applications to 3.1* on the TIBCO Developer Network web site at <http://developer.tibco.com>.

## Deprecated Features

---

This section describes deprecated features and lists equivalent features that accomplish the same result, if relevant. Any use of a deprecated feature should be discontinued as it may be removed in a future release. You should avoid becoming dependent on deprecated features and become familiar with the equivalent feature.

### Release 3.2.0

The following features are deprecated in this release.

#### Deprecated APIs

The following APIs are deprecated:

- The following `jsx3.xml.Cacheable` properties are deprecated:
  - XSL URL getters and setters
  - XSL ID getters and setters
  - XSL String getters and setters

Instead of these properties, use the XML transformers functionality: `getXMLTransformers()` and `setXMLTransformers()`.

- `jsx3.gui.insertHTML()` is replaced by `paintChild()`

#### Deprecated Prototypes

`Grid`, `List`, `Column`, and `MultiSelect` have been deprecated and moved to the **Deprecated** folder in the Component Libraries palette. `Matrix` and `Matrix Column` components replace `Grid`, `List`, and `Column`. See [Matrix Components](#) on page 13.

### Release 3.1.0

The following features are deprecated in this release.

- **Class Structure** The class hierarchy has been completely reorganized in this release. This has resulted in the deprecation of many classes. Refer to the API documentation for the list of deprecated classes and their replacements.

- `jsx3.out` is replaced by `jsx3.log()` and class `jsx3.util.Logger`. For information on these features, see *General Interface Logging* at the TIBCO Developer Network web site at <http://developer.tibco.com>.
- **Event Model** Static access to the current event object (`jsx3.EVENT`) was deprecated. In addition, in order to support both the 3.0 and 3.1 model event protocols simultaneously, many methods have been either deprecated or made to branch based on which event protocol is in use. Methods have been deprecated or renamed when they existed solely to generate a model event or when their names implied that they generated a model event. Preexisting methods that have different behavior based on the model event protocol are considered branching methods. For more information, see *Model Events* on the TIBCO Developer Network web site at <http://developer.tibco.com>.
- **Various Methods and Fields** Consult the API documentation in General Interface Builder Help for other deprecated methods and fields. Deprecated members are indicated with a strike-through font.

## Migration and Compatibility

---

To migrate projects from previous General Interface releases, see *TIBCO General Interface Migration* in the General Interface documentation.

## Closed Issues

The table in this section list issues that were closed in the named releases.

| Closed in Release         | Defect # | Summary (Sheet 1 of 11)   |
|---------------------------|----------|---|
| <b>Charting</b>           |          |   |
| 3.3.0                     | 1-7XM18V | Any change to a chart's axis property that resulted in a negative computed value of the axis Left position ran the risk of generating -1INF (negative infinity) on Internet Explorer. This caused deserialization to fail.  |
| 3.1.1                     | 1-6YXIXS | Events on chart series (and possibly other chart components) fired twice. The event handlers were incorrectly painted in the group containing the category shapes. They should have only been painted in the category shapes themselves.  |
| 3.1.0                     | 1-5ZWDAG | When an empty area chart was created, an error was generated. This error occurred when there wasn't any data to display on chart axes.  |
| <b>Data Mapping Tools</b> |          |   |
| 3.3.0                     | 1-7XA156 | The <code>jsx3.net.Service</code> class subscribed to the <code>onresponse</code> event of its <code>jsx3.net.Request</code> object during the <code>doCall()</code> method. This meant that reusing the same service instance to make multiple calls resulted in the <code>onsuccess</code> method being called multiple times (an extra time for every time <code>doCall</code> is made).   |
| 3.3.0                     | 1-7X3AN7 | The <code>jsx3.net.Service</code> class was improperly sending the string value 'null' when a CDF attribute mapping was generating a value in the outgoing request. If the CDF attribute node was missing, no value should be set. If the CDF attribute node was an empty string, the value should be an empty string.  |
| 3.3.0                     | 1-7X3AFK | The <code>doCall()</code> method for the <code>jsx3.net.Service</code> class failed to include the XML prolog when sending request documents. This wasn't standard and could cause the request to be mishandled by the receiving server. The prolog should include <code>&lt;?xml version="1.0" ?&gt;</code> , should be sent with <code>doCall()</code> requests, and should also appear when using the Test Interface in the XML Mapping Utility (panel 2 in the Test Interface). |

| Closed in Release | Defect # | Summary (Sheet 2 of 11)  |
|-------------------|----------|--|
| 3.3.0             | 1-7VF6FY | When the XML Mapping Utility parsed an XML document (not a WSDL), the <code>xmlns</code> nodes in the pattern master were persisted as CXF rules. The <code>xmlns</code> nodes should have been ignored and not persisted as rules. This was incorrect and broke the service class when the given ruleset was run.   |
| 3.3.0             | 1-7C0PJX | Nodes were missing in the XML Mapping Utility. This occurred when a WSDL referenced a schema, which in turn referenced another schema. The XML Mapping Utility didn't support this feature and the behavior was as expected. The <code>xsd:extension</code> element won't properly parse if the element was based upon an <code>xsd:extension</code> element that was based upon yet another <code>xsd:extension</code> element. |
| 3.3.0             | 1-7VF6D9 | SOAP messages that didn't define a <code>soap:operation</code> node in the WSDL caused a null pointer exception in the XML Mapping Utility. The XML Mapping Utility needed to allow messages that didn't contain this node and continue parsing.   |
| 3.3.0             | 1-7VF6EC | When the XML Mapping Utility parsed a WSDL that contained a schema-defined node with the <code>nullable</code> attribute, the attribute wasn't honored. The <code>nullable</code> attribute, if explicitly declared, should have been added to the list of restrictions for the given node when it was first parsed by the XML Mapping Utility.  |
| 3.2.0             | 1-79SFGL | No alert occurred when the XML Mapping Utility tried to parse a mapping file that didn't exist. The error message reported that the type was unrecognized when it should have reported the file wasn't found.  |
| 3.2.0             | 1-768GLZ | Static service calls using <code>setInboundURL()</code> and <code>setOutboundURL()</code> don't work. For Inbound mappings to run, the HTTP status code must be 200, 202, or 0. This affected the <code>Service</code> class when running in <code>test/static</code> mode.  |
| 3.2.0             | 1-76D12H | Added support to the XML Mapping Utility to handle WSDLs created by BW 5.3.2.  |
| 3.2.0             | 1-72BKSN | The XML Mapping Utility didn't account for different namespaces when the element name was the same.  |
| 3.2.0             | 1-71UVED | The XML Mapping Utility ignored locally declared namespaces (those namespaces declared on a node), so it failed to see the data type for the part.   |

| Closed in Release    | Defect # | Summary (Sheet 3 of 11)  |
|----------------------|----------|--|
| 3.2.0                | 1-6Q2SLD | Used an asynchronous call for the XML Mapping Utility to keep the browser from locking up if the WSDL was unavailable. Provided a Cancel button so the user could cancel if the call was taking too long.  |
| 3.1.1                | 1-6Y3BDR | Mapping Rule Migration - The CXF Rule conversion utility didn't automatically set <code>Restriction = Nillable</code> for empty nodes present in 3.0 CXF Rules.  |
| 3.1.1                | 1-6XY6MN | XML documents remained in the IDE cache after rules creation and update, and then the XML Mapping Utility was closed. These XML documents accumulated each time the XML Mapping Utility was used and closed, taking up resources.                                  |
| 3.1.1                | 1-6XY6Q4 | 3.0 Rules with POST and empty message threw errors.  |
| 3.1.1                | 1-6XY6RN | When selecting a SOAP Fault node in the mapper, an unnecessary error message was sent to the General Interface Builder log.  |
| 3.1.0                | 1-63NS8X | The SOAP Mapping Utility (now renamed XML Mapping Utility) could lose the association to the rule being edited. When this happened, the Test Rules tab stopped functioning. This behavior had no impact on runtime behaviors or performance.                       |
| <b>Deployment</b>    |          |  |
| 3.2.0                | 1-772SE3 | Select and Datepicker Heavyweight window were not anchored to the correct position when placed inside a dialog and deployed inside a portal page.  |
| <b>Documentation</b> |          |  |
| 3.3.0                | 1-7TIWOV | The API documentation incorrectly stated that the Matrix <code>getSortPath()</code> and <code>setSortPath()</code> methods required the name of the attribute to be preceded by an @ symbol. The @ symbol wasn't required and would break the sort if it was used. |

| Closed in Release                | Defect # | Summary (Sheet 4 of 11)   |
|----------------------------------|----------|---|
| <b>Firefox</b>                   |          |   |
| 3.2.0                            | 1-77QPS3 | <p>When accessing data across multiple domains on Firefox 1.5.x in Windows and Mac, an exception was thrown. For example, this occurred when running the WSDL_Mapping_2 sample application.</p> <p>For Firefox, you must configure proxy communications. See Configuring Proxy Communications in the Tips &amp; Techniques document, <i>Accessing Data Across Subdomains</i>, at <a href="http://developer.tibco.com">http://developer.tibco.com</a>.</p> |
| 3.2.0                            | 1-7AP5XP | Moving the mouse over a context menu in Firefox may cause an error message in the System Log palette. This message can be ignored.  |
| <b>General Interface Builder</b> |          |   |
| 3.3.0                            | 1-7WP11F | <p>"Reset/Clear" in the <code>Matrix.ColumnFormatHandler</code> property caused the following exception:</p> <pre>15:36:35.564 global (INFO) - (IDPR02) error evaluating expression 'objJSX.setFormatHandler(vntValue);objJSX.repaint();': 'null' is null or not an object     at jsx3.ide#BJ()     at jsx3.ide#p9()</pre>  |
| 3.3.0                            | 1-7WOXL9 | When the children for a <code>LayoutGrid</code> were rearranged in General Interface Builder, the child blocks were not resized accordingly.  |
| 3.3.0                            | 1-7UM83F | Add-in component icons weren't displayed correctly in the Component Libraries palette, because <code>GI_Builder/</code> was prepended to the icon URI.  |
| 3.2.0                            | 1-6BYOQP | <code>jsx3.ide.debug()</code> statements at runtime (or Project > Run) throw a JavaScript error in the browser. This is expected behavior. To prevent these errors, wrap debug statements in an <code>if</code> statement, which refers to a global <code>isDebug</code> variable. Then set the variable to <code>True</code> for development and <code>False</code> for deployment.  |
| 3.2.0                            | 1-7A5UB3 | The cursor was missing in the General Interface Builder editor when running in Firefox.   |
| 3.2.0                            | 1-7CHI0R | When adding a new class path on the Classpath page of the Project Settings dialog (Project Settings > Classpath), an error was thrown and the new record didn't immediately display.  |

| Closed in Release | Defect # | Summary (Sheet 5 of 11)   |
|-------------------|----------|---|
| 3.2.0             | 1-78QAO1 | Unable to delete text area/textbox once it was dropped in the General Interface Builder work area toolbar (bottom of work area).  |
| 3.2.0             | 1-76FWL5 | When switching projects in General Interface Builder after an exception, General Interface Builder appeared to be unresponsive. High CPU usage was observed (99%).  |
| 3.2.0             | 1-72UPUR | The method, <code>jsx3.net.Service.getEndpointURL()</code> , appeared in API help but not when using the type-ahead feature (Ctrl+spacebar).  |
| 3.2.0             | 1-7AOYPQ | Restoring a Matrix Column from the Recycle Bin caused an exception.   |
| 3.2.0             | 1-6FEKS8 | Certain sequences of author-time events, including toggling an object's properties between Absolute and Relative, could cause strange results later when trying to move the object by dragging the object's center point. The object appeared in a different location than where it was dropped.  |
| 3.2.0             | 1-6U3XMU | <code>jsx3.GO()</code> and other methods in getting a handle to an object which do not include the namespace found objects which have been placed in the trash can. This made updates to the view at author time unpredictable.   |
| 3.2.0             | 1-6X6AG4 | When the Source XML (Expert) view of a GUI Component (2nd button on the bottom of the work area) was active, only the Project Files palette and the Local Data Cache palette should be enabled. Because other areas of the user interface were enabled, it was possible to make changes to the component using the Component Hierarchy palette or Properties Editor palette, and so on, which were not persisted. |
| 3.2.0             | 1-6X6AIS | There was no warning given when a developer tries to import a Referenced or Referenced-async GUI component as a child of JSXBODY (the topmost node in the Component Hierarchy). All referenced components needed to be a child of an object in the component hierarchy of the referencing component. Otherwise, when the referencing component was saved, the reference was lost.                                 |
| 3.1.1             | 1-70Q8JU | The Properties Editor palette got out of alignment when the Enter key was used for navigation.  |
| 3.1.1             | 1-6Z6WKR | XML markup text didn't render in the logger.  |
| 3.1.1             | 1-6Z6C5E | <code>jsx3.app.Monitor</code> didn't escape HTML/XML markup text.   |

| Closed in Release                  | Defect # | Summary (Sheet 6 of 11)  |
|------------------------------------|----------|--|
| 3.1.1                              | 1-6ZS55H | Changing the Show Deprecated Classes option collapsed the tree, unselected the current class, and prevented the selection of methods.  |
| 3.1.1                              | 1-6X6LLE | Pressing the Enter key while in the Type column of the Dynamic Properties Editor (or combo box column in any Grid) moved the focus two rows down.  |
| <b>General Interface Framework</b> |          |  |
| 3.3.0                              | 1-7YTIK0 | <p>In some versions of Internet Explorer 6 and 7, XML, XSL, and JSS files were never cached by the browser.</p> <p>For more information on Internet Explorer caching and best practices, see "Understanding Internet Explorer Caching" at <a href="http://developer.tibco.com">http://developer.tibco.com</a> in the Tips and Techniques section.</p>  |
| 3.3.0                              | 1-7XUQPP | The <code>jsx3.xml.Processor</code> constructor didn't accept <code>jsx3.xml.Entity</code> (and subclass <code>jsx3.xml.Document</code> ) for the source document parameter.   |
| 3.3.0                              | 1-7Y9EB1 | The <code>jsx3.net.Form()</code> method caused an error due to obfuscation.  |
| 3.3.0                              | 1-7U7YT1 | The <code>activateOnHotKey</code> attribute of the application monitor ( <code>logger.xml</code> ) doesn't work. It should disable the application monitor until the hot key, <code>Ctrl+Alt+m</code> , is pressed in the application.   |
| 3.3.0                              | 1-7WUUZU | The <code>jsx3.resolveURI()</code> method erroneously removed query parameters and fragment parts of the URI.  |
| 3.3.0                              | 1-7VUMGR | In Internet Explorer and over HTTP, if a component file contained a dynamically loaded class and an include that referenced another component file that also contained the same dynamically loaded class, General Interface under certain conditions showed FATAL alerts about trying to reload the class.   |
| 3.3.0                              | 1-7V4G99 | The <code>jsx3.xml.Entity.setValue()</code> method caused inconsistent behavior in the XML Mapping Utility. In Firefox, this method was concatenating the string by appending each new bit of text, while in Internet Explorer it was replacing any existing text. The correct behavior was to replace all content of the entity with the text value of the input parameter, so that the only value of the entity is the newly added text value. Firefox and Internet Explorer now consistently handle the following methods: <code>setValue()</code> , <code>createNode()</code> , <code>insertBefore()</code> , and <code>appendChild()</code> . |

| Closed in Release | Defect # | Summary (Sheet 7 of 11)   |
|-------------------|----------|---|
| 3.3.0             | 1-7V4G9S | A Tabbed Pane container with two asynchronously loaded Matrix components (asynch referenced the same matrix) that were set with the Not Selectable property caused an exception: 18:02:38.747 global (ERROR) - Uncaught Exception: Reference to undeclared namespace prefix: 'xsl'.   |
| 3.2.0             | 1-7CIEMN | In General Interface Framework, there was a problem if you used an edit mask within a Matrix and that given Matrix instance didn't use any pagination ( <code>jsx3.gui.Matrix.PAGING_OFF</code> ). Calling the <code>redrawRecord()</code> method or any method that calls <code>redrawRecord()</code> , such as <code>insertRecord()</code> or <code>insertRecordNode()</code> , resulted in an error. |
| 3.2.0             | 1-79I48Z | The Dynamic Properties editor (Matrix control) threw an exception when updating the <code>jsxid</code> column and required refresh to be in synch with underlying data.   |
| 3.2.0             | 1-73QTJ7 | Removing a child of a layout grid (and its subclasses such as <code>StackGroup</code> ) didn't properly remove the child HTML. This was true if the layout grid had been repainted but not true if the children had been added with <code>insertHTML()</code> .   |
| 3.2.0             | 1-72KUMP | Hot keys registered as properties of the button classes or registered as the <code>jsxkeycode</code> CDF attribute of menu should register themselves with the first ancestor DOM node that was a <code>jsx3.gui.Window</code> , <code>jsx3.gui.Dialog</code> , or root block of a server.  |
| 3.2.0             | 1-72G8V7 | CDF records with only numeric IDs cause ID collisions.  |
| 3.2.0             | 1-70Q86W | Added missing <code>getServer()</code> method to the <code>jsx3.net.Service</code> class, allowing for more consistent experience in both General Interface Builder and runtime.  |
| 3.2.0             | 1-712JG1 | It wasn't possible to combine nodes or documents that were created using differing threading models. The threading model used by the <code>xmlhttp</code> control and the threading model used by static XML documents were different.  |
| 3.2.0             | 1-6X3V2V | Adding more than two children to a splitter parent caused unpredictable runtime behavior.   |
| 3.1.1             | 1-72252X | <code>jsx3.net.Service.setTimeout</code> caused JavaScript error, "onTimeout is undefined".   |

| Closed in Release     | Defect # | Summary (Sheet 8 of 11)   |
|-----------------------|----------|---|
| 3.1.1                 | 1-6XP1CC | XSL document was reloaded when destroying List/Grid.  |
| 3.1.1                 | 1-6YKVJL | Date Picker failed in GMT- <i>nn</i> time zones.  |
| 3.1.0                 | 1-692LVH | The JavaScript function <code>setTimeout</code> was not supported in the version of the HTTP object referenced in Project Deployment Options.   |
| <b>GUI Components</b> |          |   |
| 3.3.0                 | 1-7XUQQU | Calling the <code>dialog.focus()</code> method on a modal dialog caused the loss of modal.  |
| 3.3.0                 | 1-7Y9EC9 | Some formats of the <code>jsx3.gui.Matrix.ColumnFormat.getInstance()</code> method didn't work.   |
| 3.3.0                 | 1-7XJ0NF | <p>Several XSLT features (particular as implemented by the Matrix) caused a noticeable slowdown. First, due to browsers not caching XSL imports, any repaint command on a Matrix (or the other CDF controls) forced a roundtrip to the server, which caused a substantial impact on even the smallest update. In addition, the Matrix should expose a public API that allows developers direct access to the native HTML element for a Matrix cell. This was critical when integrating with technologies, such as Comet, DWR, or Lightstreamer, where using XSLT for a simple update to a cell was CPU intensive.</p> <p>Added a new public method to Matrix, <code>getContentElement()</code>, that allows access to the HTML element by providing the CDF record id and the named attribute on the CDF.</p> |
| 3.3.0                 | 1-7X9FEW | Importing failed with an exception when canvas was "dirty" (after adding a new container and trying to import into its pane).   |
| 3.3.0                 | 1-7X3RV2 | The cursor for Matrix cells in Internet Explorer appeared as the text cursor ( <code>cursor:text</code> ;) except in portions of header cells where text wasn't present.  |
| 3.3.0                 | 1-7X3RSF | In Internet Explorer, unless a row in the Matrix explicitly implemented a <code>bgcolor</code> (specified in the XSL Parameters Palette or the Properties Editor palette), the text bled through onto the next cell in the row.   |
| 3.3.0                 | 1-7X3APA | The <code>jsx3.gui.Button</code> class couldn't be toggled from relative to absolute <b>and</b> have the left/top be honored.   |

| Closed in Release | Defect #            | Summary (Sheet 9 of 11)  |
|-------------------|---------------------|--|
| 3.3.0             | 1-7WS633            | With a Matrix row selected, switching the application focus to another application, such as Notepad, and then switching back to the browser caused multiple (2) select events to be triggered.   |
| 3.3.0             | 1-7WS62L            | After resizing the Properties Editor palette and the Events Editor palette by resizing the splitter pane or resizing the browser window, "Reset/Clear" a property caused the name cell to expand in size.  |
| 3.3.0             | 1-7U5AVZ            | The Space key didn't trigger select (or execute) event for a Matrix List or a Matrix Grid.   |
| 3.3.0             | 1-7T8Y2X            | A Dialog could be resized to a "floating" drag corner image by dragging the left bottom edge of the dialog to the right top edge.  |
| 3.3.0             | 1-7TLD4E / 1-7UM7XG | When a Tree was already displayed on the screen and the <code>insertRecord()</code> method was used to add the first new child record to a node, the new Tree node displayed was detached from the parent node.  |
| 3.3.0             | 1-7VK76Z            | In Internet Explorer 6, a modal dialog invoked from a menu in a layout pane wasn't rendered correctly. This occurred on initial loading of dialog and every other loading of dialog, such as third and fifth. On the second, fourth, and sixth loading of dialog, the modal dialog was rendered correctly. |
| 3.2.0             | 1-6RBJ3S            | Keyboard navigation couldn't be used with the Date Picker component, which obstructed the process of using the Tab key to select components.   |
| 3.2.0             | 1-6OUN7V            | <code>jsx3.gui.List/Grid</code> - Unselectable nodes in List/Grid could trap focus, blocking keyboard navigation past those items.   |
| 3.2.0             | 1-7RUQNG            | While dragging a record from a can drag Matrix control to another drop-enabled Matrix control, the mouse cursor is changed into a forbidden cursor (/).  |
| 3.2.0             | 1-7D33L9            | Calling the <code>setDisplay()</code> method on a Matrix Column child should result in the XSLT for the owning Matrix to be reset.   |
| 3.2.0             | 1-7CM78U            | When using a paginated instance of the Matrix ( <code>jsx3.gui.Matrix.PAGING_PAGED</code> ), if records were added and removed and the Matrix was then repainted (by calling <code>repaintData()</code> or <code>repaint()</code> ), the scrollbars didn't update to reflect the changed record count.     |

| Closed in Release | Defect #              | Summary (Sheet 10 of 11)   |
|-------------------|-----------------------|--|
| 3.2.0             | 1-78Q4ZV              | Selecting a Matrix cell on the right-hand side of the grid caused the grid to jump to the left.  |
| 3.2.0             | 1-7AMECV              | Selecting a different node in the Component Hierarchy palette while editing a property in the Properties Editor palette might have caused the change to affect the newly selected object, not the intended object.   |
| 3.2.0             | 1-79KHWA              | Using the Tab key in the Properties Editor palette after editing a value triggered an exception. The Tab key didn't work in the Matrix component.  |
| 3.2.0             | 1-785LPA              | Stack gradient color disappeared after mouse over, then mouse out.   |
| 3.2.0             | 1-785LOQ              | Stack ( ) layout had text displayed horizontally instead of vertically.  |
| 3.2.0             | 1-77QQDH              | Splitter handle custom image could fail in distributed deployments.  |
| 3.2.0             | 1-75ZTPK              | Menus bound to lists didn't always work properly, because the Object ID argument was missing from <code>jsx3.gui.Menu setMenu()</code> .   |
| 3.2.0             | 1-74NKU7 and 1-75ZTO1 | In CDF data, images in <code>tree/menu/list/grid</code> that refer to <code>JSX/images</code> or <code>JSXAPPS/application_dir/images</code> didn't resolve correctly when the <code>JSX</code> directory and <code>JSXAPPS/application_dir</code> directory didn't reside in the same directory as the launching HTML page. |
| 3.2.0             | 1-748XL9              | Dialog failed to paint content after being maximized if it was window-shaded.  |
| 3.2.0             | 1-70ZZYW              | Missing a method to unselect a selected item in Grid. There wasn't a functional equivalent to List behavior.   |
| 3.2.0             | 1-6A9E3T              | <code>jsx3.gui.Tree</code> — Key navigation in a tree followed the order of the records in the underlying CDF document. If the View was resorted using the XSL parameter <code>jsxsortpath</code> , arrow key navigation in the tree wouldn't follow the order of onscreen tree nodes, resulting in unexpected behavior.     |
| 3.2.0             | 1-6OJO49              | <code>jsx3.gui.Tree</code> - Trees with hidden root nodes took a long time to paint when they were enclosed several levels deep within other components, and the ancestor components were repainted. Setting the Show Root Node property to Hide caused 15 second repaint. Setting to Show, resulted in instant repaint.     |

| Closed in Release             | Defect # | Summary (Sheet 11 of 11)  |
|-------------------------------|----------|---|
| 3.2.0                         | 1-6XUR3U | Pressing Tab or Shift+Tab while in an open select or combo box should select the current item, close the select/combo, and move focus to the next (previous) item.  |
| 3.2.0                         | 1-6VWJ99 | jsx3.gui.Grid — Grid won't accept a drop unless the auto-expand property was set to TRUE. This resulted in an on-screen control that added extra rows to the view each time the user clicked in the last row of the Grid. |
| 3.2.0                         | 1-3HVT9B | The Properties Editor palette was missing a no border property.   |
| 3.1.1                         | 1-70Q8IS | Combo control for grid failed to check for 'null' on the 'select' event, causing quirky behavior.   |
| 3.1.1                         | 1-6XJTCH | Dialogs — Clicking a Dialog icon in the taskbar should bring the dialog forward if it wasn't forward. Instead, it minimized the dialog. The requested behavior follows that of Windows taskbar and Windows icons.         |
| 3.1.1                         | 1-6X98XH | Alerts with large text blocks didn't scroll and the OK button disappeared.  |
| 3.1.1                         | 1-6WT94Q | The Radio button prototype column didn't have a default groupname, so the radio button column didn't work as expected.  |
| <b>Installation and Build</b> |          |   |
| 3.1.1                         | 1-6ZL8JH | When overwriting an existing installation, the Installer permanently deleted user-created files (files which were not installed as part of the package).  |

## Known Issues

---

This section discusses known issues in this release.

### Mac and Firefox Known Issues

Mac OS X and Firefox have the following known issues.

- The JavaScript Step Through Debugger isn't supported in Firefox. To debug in Firefox, use the Venkman extension at <http://getahead.ltd.uk/dwr/ajax/venkman/>.
- Inconsistent scrollbar support on Mac OS X. Also if layering is used, such as a dialog layered over an application, scrollbars bleed through. This occurs whenever z-index is used. See defect 1-7SGRHB on page 46.
- For charting on Firefox with Mac OS X, some SVG behavior is unexpected. For example, text isn't always rendered properly due to clipping. This is possibly related to scrolling. See defect 1-78I4SR on page 42.
- Mac OS X accelerator keys don't always work in Firefox.
- Firefox doesn't support `jsx3.net` Form with file upload. As an alternative, set the Text/HTML property of a Block component to free form HTML containing a `form` element.
- Unexpected layout behavior in Firefox with the Block component, such as misaligned GUI components, when using relative positioning.

**Workaround** To avoid unexpected layout behavior in deployed applications, it's recommended to use Block as a container **only** if it meets **one** of these requirements:

- The Block is owned by a layout manager, such as LayoutGrid, Tab, Stack, and Splitter.
  - The Block is relatively positioned and has a width of 100%.
  - The Block is absolutely positioned.
- Overflow on a draggable object, such as a dialog, is hidden.  
**Workaround** Make the dialog visible by adding width and height.

- XPath/XSLT in Firefox
  - The XSL must meet these requirements in Firefox or it fails:  
The XSL must point to the following namespace:  
`xmlns:xsl="http://www.w3.org/1999/XSL/Transform"`  
The XSL must output valid XML. Balanced tags are required. For example,  
`<xMessage>Hello World!</xMessage>`
  - XSLT implementation does not support the namespace axis, limiting the ability to query and discover namespaces. The DOM-based interface also fails to implement this axis.
  - XSLT implementation does not support the `node-set()` method, which means that complex parameters and result tree fragments cannot be resolved.
  - XSLT implementation does not allow output escaping to be disabled, which means that escaped entities cannot be resolved during a transformation.
  - The only output formats supported for XSLT processing are HTML 4.0 and XML.

For other browser issues, see General Known Issues on page 41.

## Browser Limitations and the Margin Property

The behavior of the margin property varies by browser as follows:

- Internet Explorer applies all margins properly when the object is rendered, but if an ancestor container is ever hidden (`display:none`), the left margin is no longer honored when redisplayed.
- Firefox applies all margins if the object does not specify an overflow property (`overflow:hidden`, `overflow:auto`, `overflow:scroll`). If the object uses overflow, the top and bottom margin settings aren't honored.

In summary, margin properties are honored as follows:

- The only margin setting that is honored by all browsers in all situations is `margin-right`.
- The margin properties, `margin-top`, `margin-bottom`, and `margin-right`, are honored in all browsers if the object does not specify an overflow property of `hidden`, `scroll`, or `auto`.

- The margin properties, margin-top, margin-bottom, margin-left and margin-right, are honored in all browsers if the object does not specify an overflow property (hidden, scroll, or auto) and no ancestor of the object ever has its display property toggled between none and block.

## General Known Issues

The table in this section lists known issues in this release.

| Defect #                  | Summary/Workaround (Sheet 1 of 7)  |
|---------------------------|--|
| <b>Data Mapping Tools</b> |  |
| 1-7YL8IO                  | <p><b>Summary</b> In Internet Explorer 7 with MSXML 3.0, when you select a complex parent type in the Rules tree of the XML Mapping Utility and choose <b>Map &gt; DOM (Map and Create)</b>, the menu command fails.</p> <p><b>Workaround</b> Select a child or children of the complex parent type and choose <b>Map &gt; DOM (Map and Create)</b>.</p>   |
| 1-7YQOBJ                  | <p><b>Summary</b> Internet Explorer crashes when executing the following steps:</p> <ol style="list-style-type: none"> <li>1. Open the XML Mapping Utility.</li> <li>2. Select an output attribute.</li> <li>3. In the Mappings section, click the first down arrow triangle.</li> <li>4. Select Script.</li> <li>5. Move the XML Mapping Utility window by dragging the title bar.</li> </ol> <p><b>Workaround</b> Move the XML Mapping Utility to the desired position before executing the above steps.</p> |
| 1-70DGBK                  | <p><b>Summary</b> While retrieving and parsing a remote WSDL document in the XML Mapping Utility, if the developer makes a typo in the URL, General Interface Builder locks up until the server returns a "document not found" error.</p> <p><b>Workaround</b> Do not make typos in the URL field or work from a local copy of the WSDL.</p>   |
| <b>Documentation</b>      |  |
| 1-7Z3209                  | <p><b>Summary</b> The <code>Matrix.Column</code> documentation is missing from API help (Help &gt; API Documentation).</p> <p><b>Workaround</b> Open the documentation from this location—<br/><code>GI_HOME\doc\html\api\jsx3\gui\Matrix.Column.html</code>.</p>  |

| Defect #                         | Summary/Workaround (Sheet 2 of 7)  |
|----------------------------------|--|
| 1-7T8VF1                         | <b>Summary</b> Not all classes that extend Block implement all of the methods or input types available to Block. In these cases, the API documentation lists those methods. The Properties Editor palette accepts and displays only the correct members.   |
| 1-7SPC40                         | <b>Summary</b> When running in XHTML mode, API help throws an exception if the inline comments in the API documentation are not XHTML-compliant. For example, API help for <code>jsx3.app.Server.getEnv()</code> triggers an exception.  |
| <b>Firefox</b>                   |  |
| 1-78I4SR                         | <b>Summary</b> On a Mac, text in charts on Firefox 1.5.x doesn't display properly. The text is drawn correctly but after dragging the parent, it isn't redrawn. In some cases, text is drawn when the scroll bar is scrolled. This defect has been reported to <a href="https://bugzilla.mozilla.org/show_bug.cgi?id=316564">https://bugzilla.mozilla.org/show_bug.cgi?id=316564</a> .   |
| 1-7T87PZ                         | <b>Summary</b> On Firefox, when you drop a charting component onto the work area and try to shift focus to that component using the Show/Hide Focus Rectangle button, the charting component doesn't get the focus. Hence you can't drag-and-drop the component as desired. This defect has been reported to <a href="https://bugzilla.mozilla.org/show_bug.cgi?id=360141">https://bugzilla.mozilla.org/show_bug.cgi?id=360141</a> . |
| 1-74L8YJ                         | <b>Summary</b> General Interface Builder error sound does not play properly in Firefox 1.5.x.<br><b>Workaround</b> Download and install a plug-in for .wav files.  |
| 1-7A9DSG                         | <b>Summary</b> Firefox can't open non-XML files encoded as UTF-16.<br><b>Workaround</b> Use the General Interface Builder IDE, Internet Explorer, or a text editor to convert to 8-bit encoding before opening in Firefox.   |
| <b>General Interface Builder</b> |  |
| 1-7YL8GT                         | <b>Summary</b> In the Properties Editor palette, when you select a property value from a drop-down menu, the same selection displays for other properties with drop-down menus. For example, for Block, click in the Visibility property field and Visible displays as the value. Click on other properties that also have drop-down menus, such as Can Drag From and Can Drop On. They also display the value, Visible.             |
| 1-7Y9ZJR                         | <b>Summary</b> The Font Weight property for the toolbar button isn't working properly.   |

| Defect # | Summary/Workaround (Sheet 3 of 7)  |
|----------|--|
| 1-7T33C9 | <p><b>Summary</b> On Mac, menu accelerator hot keys aren't working for some General Interface Builder menu items. For example, IDE Settings (Ctrl+), Project Settings (Ctrl+Shift+), and all palettes(Ctrl+1, Ctrl+2, and so on). This defect has been reported to <a href="https://bugzilla.mozilla.org/show_bug.cgi?id=106048">https://bugzilla.mozilla.org/show_bug.cgi?id=106048</a>.</p>  |
| 1-7QJTEX | <p><b>Summary</b> In Internet Explorer, you can't create a new folder under the C:\ root directory using the Create New Folder button while creating a workspace folder. Creating subfolders under an existing folder is not an issue.</p> <p><b>Workaround</b> Create the folder under the C:\ root directory in the Windows file manager. In General Interface Builder, choose the Browse button in the Create or Locate a Workspace dialog or in the Workspace field of the IDE Settings dialog (<b>Tools &gt; IDE Settings &gt; Paths</b>) and select the newly created folder.</p>  |
| 1-7KV0SU | <p><b>Summary</b> The work area tabs don't cascade to the next row if they exceed the viewable space.</p> <p><b>Workaround</b> Scan through the files by pressing the left and right arrow keys.</p>   |
| 1-7HWJMF | <p><b>Summary</b> When running General Interface Builder in Internet Explorer, the following steps cause an exception:</p> <ol style="list-style-type: none"> <li>6. The browser does not occupy the entire screen.</li> <li>7. The Properties Editor palette is docked on the right side.</li> <li>8. A property in the Properties Editor palette is being edited that uses a textbox mask.</li> <li>9. The developer selects the text and continues the selection off the right edge of the browser.</li> <li>10. The developer releases the mouse off the right edge of the browser.</li> </ol> <p><b>Workaround</b> Avoid the previously listed steps.</p> |
| 1-79MFUX | <p><b>Summary</b> Firefox determines the user home from the install directory and is case sensitive, even though the file system is case insensitive.</p> <p><b>Workaround</b> If you change the browser URL from C: to c:, you need to specify the user home directory again.</p>   |
| 1-6E1BI5 | <p><b>Summary</b> General Interface Builder - When working in editable text tabs (JavaScript, XML, XSL, etc.), the type-ahead context menu (activated with Ctrl+spacebar) becomes disabled under certain circumstances.</p> <p><b>Workaround</b> Click anywhere in the edit window to reset the Ctrl+spacebar listener.</p>  |

| Defect # | Summary/Workaround (Sheet 4 of 7)   |
|----------|---|
| 1-6VYSPR | <p><b>Summary</b> When General Interface Builder is launched from the HTA file, if Windows XPSP2 goes to sleep, IE will hang when the user re-logs into Windows.</p> <p><b>Workaround</b> Launch General Interface Builder from <code>GI_Builder.html</code>.</p> |
| 1-6Y33HD | <p><b>Summary</b> The Debugger will occasionally evaluate a commented line.</p>   |

| Defect # | Summary/Workaround (Sheet 5 of 7) |
|----------|-----------------------------------|
|----------|-----------------------------------|

|                                    |  |
|------------------------------------|--|
| <b>General Interface Framework</b> |  |
|------------------------------------|--|

|          |   |
|----------|---|
| 1-7Z3211 | <p><b>Summary</b> When a General Interface application is deployed to an HTTP server and the launch page for the General Interface application is not a sibling to the JSX directory, default system images, including the following aren't resolved correctly:</p> |
|----------|---|

- The plus/minus toggling icon for tree and matrix-tree
- The transparent image used for all CDF controls
- The green check mark icon used for the select options list to denote which option is selected

**Workaround** There are three possible workarounds:

- When deploying the application, make sure the launch page is a sibling to the JSX directory. The launch page, which is the web page that embeds the `script` element, loads the General Interface application.
- For tree and matrix-tree, use custom plus/minus icons. This workaround doesn't work for select and menu controls.
- Add the JSX system images that are being improperly resolved to the application directory.

For example, if in relation to the launch page, the application directory is located at `some/folder/JSXAPPS/myproject` and the JSX directory is located at `my/gi/JSX`, copy the `images` directory located at `JSX/images` to the following path:

```
some/folder/JSXAPPS/myproject/my/gi/JSX/images
```

|          |   |
|----------|---|
| 1-7T5QGX | <p><b>Summary</b> Matrix controls created in the General Interface 3.2 Beta 2 release cause "no such method" or "function required" exceptions when loaded with General Interface 3.2. This is due to obfuscated variants in the serialization files.</p> |
|----------|---|

**Workaround** Check the serialization file for obfuscated variant attributes, such as `hk=" [ ]"`. Remove these obfuscated variants manually in Source XML (Expert) view in General Interface Builder or use a text edit tool to search and remove all instances.

|                       |  |
|-----------------------|--|
| <b>GUI Components</b> |  |
|-----------------------|--|

|          |  |
|----------|--|
| 1-7YTJ1I | <p><b>Summary</b> The <code>@number,float</code> format handler no longer works.</p> |
|----------|--|

**Workaround** Use custom formatting for float, such as `@number,##0.00##`.

| Defect # | Summary/Workaround (Sheet 6 of 7)  |
|----------|--|
| 1-7YR59D | <p><b>Summary</b> Entering text in the Text/HTML property of a block in the Properties Editor palette and adding a select component to the same block, prevents the General Interface Builder tabs from working and you can't switch between tabs.</p> <p><b>Workaround</b> Use a Label component to add text to a block.</p>  |
| 1-7YR53C | <p><b>Summary</b> In Firefox, the select - combo component is truncated to a width of 113 pixels regardless of the Width property setting.</p>   |
| 1-7Y9ZKQ | <p><b>Summary</b> In Firefox, if you right-click the Size Array field of a layout component in the Properties Editor palette and select a custom created dynamic property, the following error is displayed in the System Log:</p> <pre data-bbox="332 574 1275 777">11:38:18.484 global (INFO) - (IDPR02) error evaluating expression 'objJSX.setDimensionArray(vntValue?vntValue.split(/\s*[;,]\s*/):[ ],true)';: undefined at jsx3.ide#BJ() at jsx3.ide#p9() at jsx3#eval() at jsx3.lang.Object.eval() ...</pre>                                      |
| 1-7XOKST | <p><b>Summary</b> When a project is migrated from 3.0 to 3.1 to 3.3, General Interface Builder doesn't display the component file in bold in the Project Files palette.</p> <p><b>Workaround</b> Manually update the path to use the relative path. For example, <code>components/appCanvas.xml</code>. To update the path, choose <b>Project &gt; Project Settings</b> and change the path in the Initial Component field on the Deployment page. You can also right-click the component file in the Project Files palette and choose Edit Profile.</p> |
| 1-7SGRHB | <p><b>Summary</b> On Mac OS X, if multiple dialogs are open, the vertical scroll bars of the bottom dialog bleed through to the dialog on top. This defect has been reported to <a href="https://bugzilla.mozilla.org/show_bug.cgi?id=187435">https://bugzilla.mozilla.org/show_bug.cgi?id=187435</a>.</p>   |
| 1-7DS71V | <p><b>Summary</b> The main body of the Matrix does not respond to the scroll wheel on the mouse. However, the scrollbar does respond.</p> <p><b>Workaround</b> Hover the mouse over the scrollbar to use the scroll wheel.</p>   |

| Defect #             | Summary/Workaround (Sheet 7 of 7)  |
|----------------------|--|
| 1-7XR6J9<br>1-7BPVY0 | <p><b>Summary</b> In a multiple-level menu, moving the mouse quickly in and out of a nested submenu causes the submenu to detach and move to the top left of the browser window. The problem is most apparent when the submenu is long or when the browser is repeatedly refreshed. The following exception is thrown:</p> <pre data-bbox="371 338 1313 546">12:54:06.826 global (ERROR) - Uncaught Exception: 'p.Te[...]' is null or not an object (line: 0, file: file://C:\Tibco\tibco-gi-3.3-pro\GI_Builder.html)     at jsx3.gui.Menu#_u()     at jsx3.gui.Menu.xo()     at anonymous() {       if(N.getParent()==null)return;p.Ps=null;p.FD=null;N.xo(n+1,true);}</pre> <p><b>Workaround</b> Move the mouse more slowly.</p> |
| 1-6Y5QMD             | <p><b>Summary</b> Trees which contain more than 15-20 nested levels do not render completely in the browser. Although the HTML is painted by the General Interface Framework, the browser does not render all the levels.</p> <p><b>Workaround</b> Use the Matrix components.</p>  |
| 1-754023             | <p><b>Summary</b> Cursor in text tabs bleeds through a dialog in front of it.</p>  |
| 1-6THXVP             | <p><b>Summary</b> Submenus and menus are not aware enough to always cascade in the most optimal direction. Long menus, particularly those with long submenus, at the bottom of the screen will be rendered with scrollbars.</p> <p><b>Workaround</b> Be sure to keep menus short enough and away from the bottom of the screen.</p>  |

