

TIBCO General Interface™

Release Notes

*Software Release 3.4.0
April 2007*

Important Information

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN TIBCO GENERAL INTERFACE INSTALLATION). USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document contains confidential information that is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIB, TIBCO, TIBCO Adapter, Predictive Business, Information Bus, The Power of Now, TIBCO General Interface, TIBCO General Interface Framework, and TIBCO General Interface Builder are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

THIS SOFTWARE MAY BE AVAILABLE ON MULTIPLE OPERATING SYSTEMS. HOWEVER, NOT ALL OPERATING SYSTEM PLATFORMS FOR A SPECIFIC SOFTWARE VERSION ARE RELEASED AT THE SAME TIME. SEE THE README.TXT FILE FOR THE AVAILABILITY OF THIS SOFTWARE VERSION ON A SPECIFIC OPERATING SYSTEM PLATFORM.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

Copyright © 2001-2007 TIBCO Software Inc. ALL RIGHTS RESERVED.

TIBCO Software Inc. Confidential Information

Contents

Release Notes	1
New Features	2
Release 3.4	2
Release 3.3	7
Release 3.2	8
Release 3.1.1	21
Release 3.1	21
Changes in Functionality	29
Release 3.4	29
Release 3.3	29
Release 3.2	29
Release 3.1	31
Deprecated Features	32
Release 3.4	32
Release 3.2	34
Release 3.1	34
Migration and Compatibility	36
Closed Issues	37
Charting	37
Data Mapping Tools	37
Deployment	41
Documentation	41
Firefox	41
General Interface Builder	42
General Interface Framework	45
GUI Components	48
Installation and Build	55
Samples	56
Known Issues	57
Browser Limitations and the Margin Property	57
Data Mapping Tools	57
Documentation	58
Firefox	58
General Interface Builder	60
General Interface Framework	62
GUI Components	63

Release Notes

Check the TIBCO Developer Network web site at <http://developer.tibco.com> for product information that was not available at release time.

Topics

- *New Features, page 2*
- *Changes in Functionality, page 29*
- *Deprecated Features, page 32*
- *Migration and Compatibility, page 36*
- *Closed Issues, page 37*
- *Known Issues, page 57*

New Features

This section lists features added since the last major (3.0) release of this product.

Release 3.4

This release includes several performance improvements and many productivity enhancements including:

- Faster startup load performance
- Support for one-way WSDL operations
- Multi-selection of components in the Component Hierarchy palette (drag-and-drop and multiple property editing)
- Optional workspace path for local HTTP server
- New IFrame component
- GUI component enhancements
- API Enhancements
- Localization enhancements

Read the following topics to learn more about the new features and enhancements in the release:

- Performance Enhancements on page 2
- XML Mapping Utility on page 3
- TIBCO General Interface™ Builder on page 3
- API Changes on page 5
- GUI Components on page 5
- Internationalization and Localization on page 6
- Samples on page 7

Performance Enhancements

Performance enhancements include the following:

- The General Interface™ Load Performance Optimization script, `util/gi-merge.sh`, allows you to create custom builds for your deployed applications that are optimized for load performance. See *Optimizing Load Performance* on page 225 in *TIBCO General Interface Developer Guide*.

- More efficient loading of the General Interface™ Framework due to maximized asynchronous parallel loading in the system bootstrapper.
- Optimizations to various APIs including deserialization of components, paint, and resize of GUI controls.

XML Mapping Utility

The XML Mapping Utility has the following new features and improvements in 3.4:

- Support for one-way (request, no response) WSDL operations.
- The menu command for opening the XML Mapping Utility has changed to Tools > XML Mapping Utility.
- Ability to edit the SOAP Use (encoded or literal) and SOAP Encoding (<http://schemas.xmlsoap.org/soap/encoding/>) fields in the Rule Profile panel of the XML Mapping Utility. To edit these fields, select an output or input rule in the XML Mapping Utility and select the Rule Node Profile radio button. Previously, whatever encoding was stated in the WSDL could only be changed by hand-editing the CXF.

TIBCO General Interface™ Builder

General Interface™ Builder has the following new features and improvements in 3.4:

- Ability to abort loading of the previously open editors when starting General Interface Builder. Press the **Cancel** button in the Opening Project dialog to stop loading any open editors.
- The Properties Editor palette now supports typing a dynamic property key (ID) in a Value cell, as well as selecting dynamic properties from the context menu. Dynamic properties in resource bundle files must be typed in the Value cell, because they don't display on the context menu.

- Multiple components can be selected in the Component Hierarchy palette. This new feature provides the following enhancements:
 - Support for drag-and-drop of multiple selections in the Component Hierarchy palette.
 - Allow for drop-in-place adding and rearranging of components in the Component Hierarchy palette. Children are added where dropped, not below their peers.
 - Ability to drag and move groups of absolutely positioned components in the work area.
 - Ability to clone multiple components.
 - Context menu operates on multiple selections in the Component Hierarchy palette.
- When multiple components are selected in the Component Hierarchy palette, other General Interface Builder palettes display the following behavior:
 - Properties Editor palette displays properties that are common to all selected components, allowing you to modify these properties in a single step.
 - Events Editor palette is active if all selected nodes are of the same class, allowing you to set events for multiple components.
 - Attributes Editor palette displays attributes common to all selected components, allowing you to modify attributes in a single step.
 - XSL Parameters palette displays parameters common to all selected components if they are instances of `Cacheable`. This feature allows you to modify these parameters in a single step. The Name combo box is pre-filled only if all selected components are of the same class.
 - All palettes display the text, `[multiple values]`, if the values for the selected components are different.
- Ability to set the workspace path when running the project from a local HTTP server (Project > Run Project From HTTP). This is useful if the relative path to your workspace isn't the same on the HTTP server as on disk. To set the workspace path, choose **Tools > IDE Settings > Paths** and enter the path in the WS Path field.
- A new Properties Bundle editor for authoring single-file formatted, properties bundle files has been added for localization of strings. See Internationalization and Localization on page 6.

API Changes

The new API features and improvements in 3.4 include:

Classes

- `jsx3.app.PropsBundle` class supports localized properties. See [Internationalization and Localization](#) on page 6.
- `jsx3.xml.Template` class replaces the deprecated `jsx3.xml.Processor` class. The Processor API isn't compatible with persisting a compiled XSL template, which causes inefficiencies.

Methods

- `jsx3.gui.DatePicker.focusCalendar()` - for opening a calendar.
- `jsx3.gui.Dialog.constrainPosition()` has been modified for parameterized snap behavior. This method allows you to adjust the default 32 pixel minimum amount to be displayed for a dialog after a move.
- `jsx3.gui.LayoutGrid` class has new methods and properties to extend it to two dimensions: `getRows()`, `setRows()`, `getCols()`, and `setCols()`.
- `jsx3.gui.Select.doValidate()` now verifies against the selectable value (valid `jsxid` in the CDF) instead of considering all non-null values to be valid.
- `jsx3.xml.Entity.getAttributeNames()` - returns the names of all the attributes of this node. More performant than using the `getAttributes()` method.
- `jsx3.xml.Entity.getChildIterator()` - returns an iterator that iterates over the child nodes of this node. More performant than `getChildNodes().iterator()`.
- `jsx3.xml.Entity.selectNodeIterator()` - returns an iterator that iterates over the the result of an XPath query. More performant than `selectNodes().iterator()`.

For more information, see *TIBCO General Interface API Reference*.

For deprecated APIs in 3.4, see [Deprecated APIs](#) on page 32.

GUI Components

The new features and improvements for 3.4 GUI components include:

- Timeout limit for asynchronously loaded components is increased to 60 seconds and is configurable. Use `Model.ASYNC_LOAD_TIMEOUT` to set to an optimal value for your deployment. See *TIBCO General Interface API Reference*.

- A new `jsx3.gui.IFrame` class and `IFrame` component in the Component Libraries palette makes it easier to use iframes with General Interface.
- Improved support for multiple selection in `Tree`, which includes the following:
 - Support for range selection using `Shift+click` and multiple selection using `Ctrl+click`.
 - Support for drag-and-drop of multiple records.
 - `CHANGE` model event replaces the deprecated `SELECT` event.
 - Context menu can operate on multiple rows.
 - All model events include plural forms of context variables if the action can occur on multiple records. For example, the `strDRAGIDS` context variable, which accepts string arrays, has been added for the `DRAG` event.
- `Tree` supports drag-and-drop insertion between nodes and insertion as last child of node.
- Matrix data area now responds to the scroll wheel.
- `LayoutGrid` is extended to two dimensions - column and row. Use the new `Columns Array` and `Rows Array` properties to specify column and row size. See `jsx3.gui.LayoutGrid` in *TIBCO General Interface API Reference*.
- Long menus now render with auto-scroll arrows instead of with scroll bars.
- `TabbedPane` now provides an automatic right and left scrolling mechanism for navigating through tabs that are hidden when they exceed the viewable space. Hover over the right or left arrow icons to scroll through the hidden tabs. You can also navigate tabs using the right and left arrow keys.
- `DatePicker` event interface enhancements:
 - `INPUT` event allows massaging of free form text input.
 - `SHOW` event allows the shown month to be overridden.
- `Time Picker` now responds to the number pad of the keyboard.

Internationalization and Localization

The new internationalization and localization features and improvements in 3.4 include:

- A new Properties Bundle editor for authoring single-file formatted, properties bundle files has been added for localization of strings. To create a properties bundle, choose **File > New > Properties Bundle**.
- Various locales are now included in General Interface in the `JSX/locale/` directory.

- Five GUI controls are now internationalized in General Interface: `DatePicker`, `TimePicker`, `Select`, `Menu`, and `Matrix`. `DatePicker` and `TimePicker` are localized for the locales included in General Interface. `Select`, `Menu`, and `Matrix` are localized only for English

For more information, see *Internationalizing and Localizing Applications* on page 191 in *TIBCO General Interface Developer Guide*.

Samples

Product samples have been updated to the current version. These include `Chart`, `WSDL_Mapping_1`, and `WSDL_Mapping_2`.



Create a new workspace to get the updated 3.4 sample applications. Choosing an existing workspace doesn't replace previous sample applications with updated 3.4 sample applications. This built-in functionality is designed to prevent workspace files from getting overwritten.

More samples are available at the TIBCO Developer Network at <http://developer.tibco.com>.

WSDL_Mapping_2

Because Xignite now requires registration for access to the service, the sample has been modified to run in Static mode. To receive live data, you must register with Xignite and modify the sample to run in Live mode.

Release 3.3

This release introduces the following updates:

Web Browsers

Browsers for Deployment

TIBCO General Interface applications and TIBCO General Interface™ Framework can be deployed to the following browsers:

- Internet Explorer 7.0 and 6.0.x for Windows
- Firefox 2.0 and 1.5.x for Windows, Linux, and Mac OS X

Browsers for TIBCO General Interface™ Builder

TIBCO General Interface Builder runs in the following browsers:

- Internet Explorer 7.0 and 6.0.x for Windows
- Firefox 2.0 and 1.5.x for Windows

TIBCO General Interface Documentation

The following documents now form the TIBCO General Interface documentation set:

- *TIBCO General Interface Installation* Read this manual for General Interface installation instructions.
- *TIBCO General Interface Getting Started* Read this manual for overview information and a tutorial that explains how to build a TIBCO General Interface application.
- *TIBCO General Interface Developer Guide* Refer to this manual for in-depth information about developing and deploying TIBCO General Interface applications.
- *TIBCO General Interface Component Guide* Refer to this manual to learn more about components and the Charting add-in, as well as component properties and events.
- *TIBCO General Interface API Reference* Refer to this online help content for descriptions of the TIBCO General Interface JavaScript API functions and methods.
- *TIBCO General Interface Migration* Read this manual for instructions on migrating applications from previous General Interface releases.
- *TIBCO General Interface Release Notes* Read the release notes for a list of new and changed features. This document also contains lists of known issues and closed issues for this release.

To open the documentation in TIBCO General Interface Builder, choose **Help > Help Contents**. Documentation is also available online at <http://developer.tibco.com>.

Release 3.2

This release introduces the following new features and updates:

- TIBCO Developer Network on page 9
- Web Browsers on page 9
- General Enhancements on page 11
- XML Mapping Utility on page 11

- Application Deployment on page 14
- Development Productivity on page 15
- General Interface Framework on page 17
- API Changes on page 18
- GUI Components on page 19
- Localization on page 20
- Samples on page 20
- Documentation on page 21

TIBCO Developer Network

The TIBCO Developer Network has moved to a new location. Visit <http://developer.tibco.com> for General Interface™ forums, sample applications, videos, and much more.

Web Browsers

Browsers for Deployment

TIBCO General Interface applications and TIBCO General Interface Framework can be deployed to the following browsers:

- Internet Explorer 6.0.x for Windows
- Firefox 1.5.x for Windows, Linux, and Mac OS X

Browsers for TIBCO General Interface Builder

TIBCO General Interface Builder runs in the following browsers:

- Internet Explorer 6.0.x for Windows
- Firefox 1.5.x for Windows

Browser Limitations

Some limitations in web browsers could restrict the kinds of applications which can be deployed. For known issues with browsers, see Known Issues on page 57.

General Interface API

Methods that are implementable only in specific browsers are specified in the TIBCO General Interface API documentation. Search for Firefox and Internet Explorer in the API documentation.

Charting Add-in

The Charting add-in is supported on the following browsers and platforms in XHTML and HTML pages:

- Internet Explorer 6.0.x (VML) on Windows
- Firefox 1.5.x (SVG) on Mac OS X, Linux, and Windows

For supported platform versions, see `readme.txt` in the `GL_HOME` directory.

General Enhancements

General enhancements include the following:

- Improvements to the `jsx3.gui.Select` class include:
 - Support for `@jsxstyle` and `@jsximg` CDF attributes

Use `@jsxstyle` to apply a CSS style to a record. Specify any CSS code. For example, `jsxstyle="font-weight:bold;"`.

Use `@jsximg` to reference a graphic file to use as an icon. Specify the file path relative to the project directory, for example, `images/icon.gif`. Image position depends on the component. For best results, use a 16x16 transparent GIF file.
 - Vetoable Before Select model event
- Menu hot key accelerators follow user interface guidelines for Mac OS X and Windows.
- Support for the Command key on Mac OS X has been added. Actions that require Ctrl+click on Windows translate to Command+click on Mac OS X (Ctrl+click is equivalent to right-click on Mac).
- When General Interface™ Builder opens XSL and XML files for editing, it honors their encoding.

XML Mapping Utility

The XML Mapping Utility includes these enhancements:

- Re-parse part of the rules tree. To recreate deleted nodes, right-click a node in the Rules Tree and choose Reparse to re-parse from that node down.
- Ability to choose a specific prototype for DOM projection.
- Log messages in the Mapper Log are color coded. For example, errors are red, traces are gray, and so on.
- JavaScript code generated by the XML Mapping Utility has changed due to a signature change in the `jsx3.net.Service` class. Rules files IDs are now

passed as an argument instead of URLs. See General Interface Framework on page 17.

WSDL File Browsing

The XML Mapping Utility now resolves paths to WSDLs relative to the project. It's recommended that you copy WSDLs to a `wSDL` directory in your project. Then enter `wSDL/wSDL_file.xml` in the URL field of the XML Mapping Utility.

However, if you need to resolve a path to a WSDL outside of your project, use an absolute resolver, such as `jsxuser:///` and `jsxapp:///`.

- `jsxuser:///...` Resolves relative to the parent of the JSXAPPS directory, which is the workspace. When General Interface Builder is running, this URI resolves relative to the workspace directory.
- `jsxapp://app/...` If the Server instance corresponding to the host portion of the URI is loaded into memory, the URI is resolved relative to the application base directory (`jsxappbase`).

jsx3.net.Service

The following enhancements have been made to the `jsx3.net.Service` class. For more information, see the API documentation.

- Added a new `compile()` method that allows the output mapping rules (those that handle the server's response) to be compiled into an equivalent XSLT document, which increases performance. This allows the `Service` class to use the native XSLT processor as opposed to JavaScript in order to convert the server's response to CDF. The Sample performance difference to convert 400 records from SOAP to CDF is as follows: Firefox: 0.09 seconds vs 4.0 seconds and Internet Explorer: 0.13 seconds vs 10.1 seconds.
- Updated the `doCall()` method to accept a parameter, allowing the developer to cancel the send if the outgoing message did not pass the validation rules.
- Updated the `jsx3.net.Service.setInboundURL()` and `jsx3.net.Service.setOutboundStubURL()` methods to support paths that are relative to the project directory.

For example, if the project directory for the context server is `test`, then the following valid inputs are equivalent:

- `xml/typical.xml`
- `jsxapp://test/xml/typical.xml`
- `JSXAPPS/test/xml/typical.xml`

- Added additional debug statements for more detailed debugging capabilities when running in trace mode. Error handling has also been expanded. Added a new event type that is published each time a rule in the rules file is executed, providing even greater control over how each node in a message is created or processed.

Application Deployment

The following deployment enhancements have been added:

- Accelerated load time
 - Class loading improvements

Payload size is reduced as applications now dynamically load ("lazy loading") only those classes which are needed. Classes now fall into three categories. (1) Required classes are always loaded. (2) Optional classes introduced in General Interface 3.2 classes are dynamically loaded. For example, `jsx3.gui.ColorPicker`. (3) Optional classes introduced prior to General Interface 3.2 are dynamically loaded only if the `jsx1t` deployment parameter is set to `true` in the web page that launches the application. This improves backwards compatibility. See Deployment Parameters in the Deploying Applications chapter of *TIBCO General Interface Migration*.

Use the `jsx3.require()` method to explicitly load classes synchronously. For example, debugger classes are now dynamically loaded and need to be called using the `require()` method. See Debugging on page 30.

```
jsx3.require("jsx3.ide.Debugger");
```

Specify the classpath to your classes on the Classpath page of the Project Settings dialog (Project > Project Settings).
 - Changes to how add-ins are loaded improve the load time for TIBCO General Interface Builder and General Interface applications. See Add-ins on page 30.
- Simplified portal deployment
 - Separation of `GL_HOME` from the workspace allows for easier application deployment. Choose your own workspace or use the default. Modify the workspace directory in the Workspace field on the Paths page of the IDE Settings dialog (Tools > IDE Settings).
 - Application resources are specified using relative paths, which allows for easier portability of code from one project to another and simplifies the relocating of applications in the `JXSAPPS` folder hierarchy.
 - Applications can be loaded multiple times on a single portlet page with the `jsxappns` (namespace) deployment parameter that overrides the namespace in the configuration files. See Deployment Parameters in *TIBCO General Interface Migration*.
- A loading progress indicator now displays when the General Interface Framework™ Framework loads. For multiple applications loading in the same page, only one indicator shows the loading of the General Interface™

Framework, which is shared by all portlet applications. Subordinate progress indicators show the loading of each portlet application.

To specify the type of progress indicator displayed, add the `jsxapploader` deployment parameter to the HTML `script` element on the web page that launches the application(s). For example, setting `jsxapploader=1`, is a good choice for portlets, because this would load a subordinate progress indicator. See Deployment Parameters in *TIBCO General Interface Migration*.

Development Productivity

TIBCO General Interface Builder includes the following productivity enhancements:

- The Common Interface Format (CIF) can be used to create GUI definition files on-the-fly or manually. The CIF format provides improved readability and smaller file size. TIBCO General Interface transforms these files to the current GUI XML structure for rendering. Currently, General Interface Builder can read but **not** save CIF files. Any edits made to a CIF file are saved in the standard serialization format. See Custom TIBCO General Interface Formats in *TIBCO General Interface Migration*.
- The XML/XSL Merge Tool supports opening multiple instances of the tool.
- Reorganization of options and preferences.
 - The Deployment Options dialog has been renamed to Project Settings dialog (Project > Project Settings). Project settings include deployment, add-ins, class path settings, and legacy settings.
 - The Preferences dialog has been renamed to IDE Settings (Tools > IDE Settings). Settings include IDE settings, hot keys, and user home.
- Writing and debugging code
 - The `logger.xml` file has been moved to the root of `GI_HOME` and now supports a configurable location. Use the environment variable, `jsx_logger_config`, in the `script` element of the launch page to specify

its location. See Logging and the Application Monitor in *TIBCO General Interface Migration*.

- Color coding of messages in the System Log palette, Application Monitor, and the Mapper Log in the XML Mapping Utility. For example, error messages are displayed in red and traces in gray.
- A configurable, optional sound can be triggered when messages are printed to the System Log palette. To enable sound for messages, change the `beepLevel` property in `GL_HOME\logger.xml` from `jsx3.util.Logger.OFF` to a message logging level, such as `jsx3.util.Logger.ERROR`. Sound is played for the specified logging level and higher. Firefox requires a plug-in that can play .wav files.
- JavaScript type-ahead lists (Ctrl+spacebar) are available in any code window and text areas with blue grid backgrounds. Type-ahead lists display the General Interface APIs and allow you to automatically insert package names, class names, methods, and fields.
- Component Hierarchy features: (1) Right-click a component and choose **Copy Name to Clipboard** to get the object name. (2) Right-click a component and choose **Copy Getter Code to Clipboard** to copy code for getting a handle to the object (`getJSXByName`).
- General Interface Builder now traps the Tab key in main stage code editors as 4 spaces. This is a General Interface Builder feature and does not affect runtime.
- When restoring a child component from the Recycle Bin, if the parent is gone, the child is restored to <ROOT>.
- General Interface Builder has been rearchitected for improved load performance.
- General Interface Builder keyboard shortcuts can be configured in the IDE Settings dialog (Tools > IDE Settings > IDE Hot Keys).
- Running General Interface Builder and projects
 - Ability to launch General Interface Builder in XHTML or HTML mode. Choose `GI_Builder.xhtml` or `GI_Builder.html` from `GL_HOME`. Running

in XHTML mode is useful for developing and testing applications that run in XHTML pages, such as portlet applications.

- When General Interface Builder is run in XHTML mode, an error message is output when the Text/Html property contains non-compliant code.
- Choosing Project > Run Project, runs the project in the same mode as TIBCO General Interface Builder. For example, if General Interface Builder is running in XHTML mode, the project also runs in XHTML mode.
- Run your project from a local HTTP server. Choose **Project > Run Project from HTTP**. The deployed project relative path must match the local drive relative path to shell.html for this run option to work.
- Run Project warning displays if any open tabs have unsaved changes. A dialog displays a warning that some files are not saved and allows you to Run Without Saving, Cancel, or Save and Run.

General Interface Framework

TIBCO General Interface Framework includes the following changes:

- The `persistAll` argument has been added to the `toXML()` method of the `jsx3.app.Model` class, which causes the returned serialized form to include DOM nodes with transient persistence. This is useful when you want to save the exact state of the application for troubleshooting purposes.
- Rules file IDs are now passed as an argument to `jsx3.net.Service` instead of URLs. If rules files are moved to new locations, there's no need to update the URL, because the ID is used instead. The `objService` variable generated by the XML Mapping Utility has a signature change and now accepts three arguments: server, resource ID, and operation name. The new syntax is:


```
var objService = ServerName.loadResource(Project_Resource_File_Id);
objService.setOperation(Operation Name);
```
- The new Matrix component provides an `insertBefore()` method and a visual control for dragging and dropping multiple records to a new location.
- Instantiate CDFs directly without using a GUI control with the new `jsx3.xml.CDF.Document` class. See API Changes on page 18.
- User-defined XSL properties, `jsx1` through `jsx10`, have been added to `jsx3.gui.Matrix`.
- Performance improvements to the `Array.join()` method instead of String concatenation for the `String.fromBase64()` and `String.toBase64()`.
- The `Form` class provides an API that allows you to see the hidden iframe where the HTML for the form post is being built and where the response comes back from the server.

API Changes

The following changes have been made to the TIBCO General Interface API. Search for "3.2" in *TIBCO General Interface API Reference* in the online help.

- `jsx3.app`
 - `jsx3.app.AddIn` A class that represents a JSX add-in. The JSX system creates an instance of this class for every add-in that is loaded.
 - `jsx3.app.Properties` Represents a repository of dynamic properties. Dynamic properties are simply name-value pairs. Dynamic properties can be loaded from an XML file in the CDF dynamic property format.
- `jsx3.gui`
 - `ColorPicker` A GUI class that allows the user to pick a color using an HSB (hue-saturation-brightness) picker. See `jsx3.gui.ColorPicker` in the API documentation.
 - `HotKey` Encapsulates a keydown event listener that is invoked by a certain combination of keys pressed simultaneously.
 - `Image` Renders an image. See `jsx3.gui.Image` in the API documentation.
 - `Matrix` and `Matrix.Column` See Matrix Components on page 19.
 - `TimePicker` See Time Picker Component on page 19.
 - `Window` Allows for rendering a branch of the DOM of an application in a separate browser window. This is similar to the implementation of the TIBCO General Interface Builder API documentation window.
- `jsx3.net.Service` See `jsx3.net.Service` on page 12.
- `jsx3.net.URIResolver` interface An interface specifying the methods necessary to define a context against which URIs are resolved.
- `jsx3.util`
 - `DateFormat` Formats and parses dates according to a token-based string format. This class is fully localized.
 - `Locale` Represents a region of the world. Other classes may be localized, meaning that their behavior depends on their assigned locale.
 - `MessageFormat` Constructs localized messages from a pattern and parameters. A message format takes a list of arguments, formats them, and inserts them into the pattern at specific places.
 - `NumberFormat` Formats and parses numbers.
- `jsx3.xml.CDF.Document` A subclass of `jsx3.xml.Document` that implements the CDF interface. This class exposes the CDF convenience

methods on an XML document and allows you to work directly with a CDF document, without needing to work with a GUI list control. Use this class for adding records and so on.

- `jsx3.xml.Cacheable` XML Transformers replace XSL ID, XSL URL, and XSL String:
 - `getXMLTransformers()`
 - `setXMLTransformers()`

GUI Components

The classes, `jsx3.gui.Grid`, `jsx3.gui.Column`, and `jsx3.gui.List`, have been deprecated and are not supported in Firefox. The new Matrix classes, `jsx3.gui.Matrix` and `jsx3.gui.Matrix.Column`, have replaced the deprecated classes. New Matrix prototypes are available in the Component Libraries palette. See [Deprecated APIs](#) on page 34.

Tree Component

The Tree prototype has been moved to the Miscellaneous folder of the Component Libraries palette.

Matrix Components

New Matrix components, which are composites of the List, Grid, and Tree components, provide richer functionality. Matrix is fully supported in Firefox and Internet Explorer. It's recommended that you use Matrix instead of Grid, Column, and List as they have been deprecated.

These components support such features as dynamic loading of lists for better performance, tree rendering of 100 levels deep, hierarchical lists that behave like trees, multi-column trees that behave like lists, and many other features. For more information, see `jsx3.gui.Matrix` and `jsx3.gui.Matrix.Column` in *TIBCO General Interface API Reference* and *Using Matrix Components in TIBCO General Interface Migration*.

Time Picker Component

The new TimePicker component, `jsx3.gui.TimePicker`, is a clock for selecting the hour, minute, and AM or PM. Seconds, milliseconds, and a 24 hour clock can also be displayed. This control is localized.

New GUI Controls and Behaviors

- Color Picker allows the user to pick a color using an HSB (hue-saturation-brightness) picker.
- Date and Time Picker support keyboard navigation into and out of controls, as well as within the controls.
- Date Picker permits typing of date value into the DatePicker box as an alternative entry method.
- Paint methods are now XHTML compliant.
- Drop-downs for combos and selects can be wider than the unexpanded control.
- Insert stack and tab children in a specific location. See these methods of the `jsx3.app.Model` class in the API documentation: `insertBefore()`, `getFirstChild()`, `getLastChild()`, `getNextSibling()`, and `getPreviousSibling()`.
- Combo now has a `maxLength` property and method.

Localization

This release includes several new localization features:

- Date, time and number formats are now externalized in the `MessageFormat`, `NumberFormat` and `DateFormat` classes. For more information, see the new `jsx3.util` API classes for localization in General Interface Framework on page 17.
- A new deployment option, `Default Locale`, for setting language and country codes for localizing applications.

Samples

Product samples have been updated to the current version. These include `Chart`, `WSDL_Mapping_1`, and `WSDL_Mapping_2`.



Choosing an existing workspace doesn't replace previous sample applications with updated 3.2 sample applications. This built-in functionality is designed to prevent workspace files from getting overwritten. Create a new workspace to get the updated sample applications.

More samples are available at the TIBCO Developer Network at <http://developer.tibco.com>.

Documentation

This release includes the following changes to documentation:

- *TIBCO General Interface Builder GUI Reference* has been updated and included in this release.
- *TIBCO General Interface Builder Chart User's Guide*:
 - Chapter 1, *Working with Charts*, has been moved to *TIBCO General Interface Builder Getting Started Guide*.
 - Chapter 2, *Chart Components*, has been moved to *TIBCO General Interface Builder GUI Reference*.
 - *TIBCO General Interface Builder Chart User's Guide* has been removed.
- Class property descriptions have been added to the Properties Editor palette. Hover over a property, such as *Padding*, to see a description of it in the spyglass.

Release 3.1.1

This release introduces the following enhancements:

- The XML Mapping Utility's *Generate Code* button is now a menu button, which introspects for the available operations. If the rule file has not been saved, selecting an operation triggers an alert which says to save the file. Only when the rule file has been saved does the code generator put the code on the clipboard and alert the user to paste the code to the desired location.
- The signature for the `Model.loadXML()` method now accepts `jsx3.xml.Document` as well as `string`. Without this method the developer cannot pre-cache GUI components in the cache to avoid run-time reloading.

Release 3.1

This release introduces a wide variety of new features in the following categories:

- XML Mapping Utility on page 22
- Package Reorganization on page 22
- Usability Enhancements on page 24
- Logging on page 25
- Event Model on page 25
- GUI Components on page 26
- Help on page 28

XML Mapping Utility

- Expanded support, including:
 - WSDL (Document-Literal and RPC-Encoded)
 - Schema (2001)
 - XML/XHTML (including RSS, REST, and so on)
- Step-through tester with detailed logging, describing each node as it is processed by the XML Mapping Utility.
- Automatic UI projection. Fields described in a WSDL (or any other source format) can be leveraged by the XML Mapping Utility to create the auto-generate the GUI.
- Improved logging support with detailed information about why a mapping may have failed, including unsupported schema nodes, malformed XML, improper imports, and so on.
- Support for offline testing and configuration, allowing the mappings to be built and tested without accessing the live services.
- Automatic migration of 3.0 maps to the new 3.1 format.
- Test message generator, capable of simulating the live service.

See the *TIBCO General Interface Builder Getting Started Guide* for information on many of these features.

Package Reorganization

jsx3 The `jsx3` package contains the deprecated classes from General Interface™ 3.0. Most of these classes have been moved into one of the following packages: `app`, `gui`, `net`, `util`, and `xml`. These classes can still be referred to by their old names; however this is deprecated and not guaranteed to work in future versions.

jsx3.app The `jsx3.app` package contains classes related to General Interface applications. Classes in this package are used extensively in application JavaScript code.

The `Server` class is the controller in the JSX architecture. An instance of this class is created by the JSX runtime for each loaded application. `Server` provides access to the application DOM (`getRootBlock()`, `getDOM()`, `getJSX()`, and so on), the application cache (`getCache()`), and application settings (`getSettings()`).

The `Monitor` class, new in 3.1, is a vital tool in debugging running applications. It brings the power of the TIBCO General Interface Builder system log to running applications by displaying logging messages in a separate browser window.

jsx3.chart The `jsx3.chart` package contains all the classes contained in the General Interface Charting add-in. This package provides a collection of GUI controls that render charts. Bar, column, area, line, plot, bubble, pie, and doughnut charts are supported.

The General Interface Charting add-in provides the following features:

- Prototype charts effortlessly in TIBCO General Interface Builder, just like any other GUI control
- Render from any standard CDF data source as a chart
- A rich event model for implementing interactive charts
- Offload chart rendering to the client browser, no plug-in required

jsx3.gui The `jsx3.gui` package contains all the GUI controls available by default in the JSX runtime. Classes in this package are typically not instantiated by the developer. Rather they are prototyped in TIBCO General Interface Builder, serialized to component files, and deserialized at application runtime by the JSX runtime. TIBCO General Interface Builder provides at least one prototype for each class in this package.

General Interface 3.1 contains the following new GUI controls:

- `ImageButton` A simple button class comprised of a separate image file for each state of the button.
- `Slider` A form control comprised of a track and a handler that is draggable along the track.
- `Sound` Provides a standard interface for playing sounds of different formats.

jsx3.lang The `jsx3.lang` package contains the classes that comprise the General Interface class, inheritance, and introspection model. This model, introduced in General Interface 3.1, extends JavaScript 1.5 with the following features:

- A simple syntax for declaring classes, with support for “extends” and “implements”
- Mixin interfaces
- An extended base class, `jsx3.lang.Object`, from which all other classes descend
- Fully introspectable classes, interfaces, packages, and methods
- A base exception class, `jsx3.lang.Exception`, with stack tracing facilities
- Access to the overridden method determined by context, with the `jsxsuper()` and `jsxsupermix()` methods

Developers who use this package, rather than the typical facilities provided by JavaScript 1.5 to define custom classes will tap the significant developer-friendly features provided by this package.

jsx3.net The `jsx3.net` package contains various classes related to HTTP communication. Applications that use the data mapper and/or communicate with web services or legacy HTTP forms will use the classes in this package extensively.

`Form` allows a General Interface application to submit to legacy HTTP forms by either GET or POST and allows for file upload to such forms. `Request` is a platform independent wrapper of the browser XMLHTTP control. It allows any XML data source to be fetched either synchronously or asynchronously. `Service` is the programmatic interface onto the data mapping utility. `URI` is a simple utility class that is useful for parsing and resolving URIs.

jsx3.util The `jsx3.util` package contains various utility classes.

`EventDispatcher` is a mixin interface that when implemented by a class provides functionality according to the publish-subscribe design pattern. The `Logger` class, new in General Interface 3.1, is the primary interface of the General Interface logging system.

jsx3.xml The `jsx3.xml` package contains various classes related to XML processing.

The `Document`, `Entity`, and `Processor` classes provide platform independent interfaces onto the native browser XML DOM and XSLT libraries. `CDF` is a mixin interface, implemented by all CDF GUI controls, that provides an object-oriented interface onto the CDF XML format. `Cacheable`, also implemented by many GUI controls, is a mixin interface that provides functionality related to fetching and storing XML and XSL documents in the application cache.

Usability Enhancements

- TIBCO General Interface Builder can now be launched using `GI_Builder.hta` file in `GI_HOME`. When launched using this file, the browser menus and browser toolbars are hidden, leaving maximum screen area for development tasks.
- Tree components now support selecting multiple nodes. A new Multi-Select property for enabling or disabling this feature was added. When the property is set to Multi-Select, users can press the Ctrl+click to select multiple nodes in the hierarchy.

This change also allows you to select multiple items in the Local Data Cache palette and Project Files palette in TIBCO General Interface Builder, as well as the Rules Tree in the XML Mapping Utility.

- **Palette features** The XSL Parameters and Attributes Editor palettes are now hidden by default. You can display these palettes by manually selecting them in the Palettes menu.

The state and position of floating palettes is now stored as a project setting in TIBCO General Interface Builder, and preserved across project sessions. If a palette is floating when a project is closed, when the project is reopened the palette is still floating in the same position.

Projects

- TIBCO General Interface Builder projects can now be located in subfolders. In the Create New Project dialog, specify the project name as *project_path/project_name*, where *project_path* is one or more directory names under the *GI_HOME/JSXAPPS* directory. Separate directory names with forward slash characters (/).
- A new option for specifying whether TIBCO General Interface Builder automatically opens the last project on startup was added to Tools menu.
- Project files that begin with the string `jsx` are now supported in TIBCO General Interface Builder.
- A new Watermark field for moving the Powered By TIBCO text string to the left, center, or right side of your application window was added to the Project Deployment Options dialog.

Logging

This release contains a new logging system defined in the `jsx3.util.Logger` class and a new `jsx3.app.Monitor` class for displaying logging messages in a separate browser window. For details, see the online API help in TIBCO General Interface Builder.

For more information and code samples, check the TIBCO General Interface Developer Community at <http://developer.tibco.com>. See the document *Advanced Logging*.

Event Model

This release introduces significant changes to the way that application components handle events. The global event object (`jsx3.EVENT`) is deprecated. For API calls and user interactions that interact with events, the new model requires explicitly passing the event object, an instance of `jsx3.gui.Event`. For more information and code samples, check the TIBCO General Interface Developer Community at <http://developer.tibco.com>. See the document *Model Events*.

These changes are implemented in a backward-compatible manner, so that immediate migration is not necessary. Existing projects and applications run seamlessly without modification. However, new projects use the new event protocol unless the Event Protocol field is set to 3.0 in the Deployment Options dialog.

GUI Components

- TextBox and Password prototype components have a new Max Length property for specifying the maximum number of characters a user can type in a text box or password field.
- Select and Combo components support for the XSL attribute `jsxshallowfrom` for specifying a portion of a CDF structure to render in the component. Previously, any hierarchy information in CDF data was not shown by these components. You can add this parameter using the XSL Parameters palette, which can be accessed using the Palettes menu. To display only CDF records that are children of the root element, specify `jsxroot`.
- Tree components support a new `jsxdeepfrom` XSL parameter for specifying the `jsxid` value of the first visible node in the tree. All descendants of this node are also displayed, while the root node remains hidden.
- Support for the `insertHTML` method was added to the `jsx3.gui.Stack` and `jsx3.gui.StackGroup` classes for more efficient painting.
- Select and Combo components now support the `jsxtip` system attribute in the CDF document. This attribute provides tooltip text when the user hovers the mouse cursor over the component.
- The Block and BlockX components now support a double-click event, which allows images and labels to be used as buttons. The `setTip()` method was also enhanced to automatically repaint tooltip text. For information on descendant components, see the description of `jsx3.gui.Block` in the online API help.
- A new class, `jsx3.gui.ImageButton`, was added with support for image rollover, and for relevant events. A different image can be used for each button state. For details, see the class description in the online API help.
- Other new API classes in this release include `jsx3.util.Sound` and `jsx3.gui.Event`.
- **List and Grid components** The List and Grid prototype components have been enhanced as follows:
 - **New events** The Before Sort and After Sort events fire just before or after a user sorts the contents of a List or Grid component. Before Sort also allows the index value of the clicked column to be modified before the data is

sorted. After Sort can be used to perform cleanup tasks after data is repainted.

Similarly, the Before Resize and After Resize events fire when a user resizes the component. Resizing a component with many data rows can be canceled, or on-screen dimensions can be modified to optimize the display.

- **Attributes for XSL parameters** Support for 4 new XSL attributes was added. You can add these parameters using the XSL Parameters palette, which can be accessed using the Palettes menu.

`jsxshallowfrom` allows you to specify a portion of a CDF structure for rendering in non-hierarchical GUI components, such as List and Grid. Previously, any hierarchy information in CDF data was not shown by these components. Specify the name of the immediate parent element for this attribute. To display only CDF records that are children of the root element, specify `jsxroot`.

`jsxbg1` allows you to specify the background color of odd-numbered rows, beginning with the first row. `jsxbg2` allows you to specify the background color of even-numbered rows, beginning with the second row.

`jsxstyle` allows you to specify any valid CSS style for a record. Only the record that includes this attribute uses the specified style.

- **Additional checkbox state** CheckBox components can be selected, unselected, or partially selected. The new partially selected state can be programmatically set, for example to select a parent object in a nested list when a child object is explicitly selected. To indicate the partial selection state, the checkbox displays a minus sign (-) character.
- **Select and Combo components** The tab and arrow keys can now be used to navigate in the list of values and select a value. The type-ahead feature can be used for narrowing the list of values in a Combo component, provided the `jsxid` and `jsxtext` attributes have identical values in the CDF file used by the component.
- **Slider component** A new class, `jsx3.gui.Slider` and a new prototype component, Slider (H) were added. Use a slider to allow users to set a numerical value in a defined range. Clicking in the slider bar moves the handle to the clicked location. Dragging the handle changes the slider value.
- **API methods for masking** The `showMask` and `hideMask` methods were added to the `jsx3.gui.Block` class. These methods can be used to hide or disable any area of the screen. An optional message can be displayed.

Help

- A link to information on writing regular expressions was added to the Help menu in TIBCO General Interface Builder. To access this web page, select **Help > Internet Resources > Regular Expressions Guide**.
- **API reference**
 - Better visibility of JavaScript native functions, navigable type links, and automatic search cancellation when the window is closed during a search operation.
 - A menu in the API help window was added with a existing option, Show Inherited Members, and a new option, Show Deprecated Classes and Members.
 - An HTML version, displaying in a separate browser window, is now available.

Changes in Functionality

This section discusses changes in functionality since the last major release of this product.

Release 3.4

General Interface 3.4 includes the following changes in functionality.

Application Deployment

The following deployment feature has been removed in 3.4:

- The `jsxlt` deployment parameter has been removed and is no longer supported. If you've deployed applications using `jsxlt="false"`, see *Migrating Projects from 3.2 or 3.3 to 3.4* on page 21 in *TIBCO General Interface Migration*.

Release 3.3

In some versions of Internet Explorer 6 and 7, XML, XSL, and component serialization files may not always be refetched from an HTTP/S server even if they have changed on the server.

For more information on Internet Explorer caching and best practices, see "Understanding Internet Explorer Caching" at <http://developer.tibco.com> in the Tips and Techniques section.

Release 3.2

Every effort has been made to provide backward compatibility from General Interface 3.2 to 3.1. However, some migration steps are required. For migration instructions, see *TIBCO General Interface Migration*.

TIBCO General Interface Framework

- For more flexibility in project deployment, the following changes have been made:
 - Projects are now saved to a workspace directory. The *workspace* is the directory that contains your projects, custom add-ins, custom prototypes, and your user settings for General Interface Builder. You can create a new workspace, choose an existing directory, or use the default directory. To

change the workspace, choose **Tools > IDE Settings > Paths** and specify the path in the Workspace field.

- The launch page and `JSXAPPS` and `JSX` folders can each be in any location on the server.

See Application Deployment on page 14.

- Debugging

- Debugger classes are now dynamically loaded. You must use the `jsx3.require()` method before any `jsx3.ide.debug()` statements to load debugger classes. For example,

```
jsx3.require("jsx3.ide.Debugger");
```

- Add-ins

To accelerate TIBCO General Interface Builder and GI application load time, add-ins are only loaded when required.

- By default, add-ins, such as Charting, are no longer loaded automatically. Add-ins must be enabled in the project to have access to those features. To enable add-ins, choose **Project > Project Settings > Add-ins**. Select the add-in, Save, and restart TIBCO General Interface Builder.
- The Mapping add-in is always available and doesn't need to be enabled in the Project Settings dialog.
- An `addin` directory has been added to the workspace for storing any custom add-ins you create. These add-ins aren't loaded unless enabled in the project.
- How some properties are specified has changed. Left, Top, Width, and Height properties can be specified in implied pixels or in percentages. Padding, Margin, and Border properties have also been updated. Use the abbreviated TIBCO General Interface syntax for better performance or use the CSS2 syntax. See Entering CSS Values in *TIBCO General Interface Migration*.

TIBCO General Interface Builder

The Deployment Options dialog and the Preferences dialog have been renamed and some new options added. See Reorganization of options and preferences. on page 15.

Release 3.1

Every effort has been made to provide backward compatibility from General Interface 3.1 to 3.0. In most cases applications will work with no changes. For more information on migrating 3.0 projects to 3.1, see *Migrating 3.0 Applications to 3.1* on the TIBCO Developer Network web site at <http://developer.tibco.com>.

Deprecated Features

This section describes deprecated features and lists equivalent features that accomplish the same result, if relevant. Any use of a deprecated feature should be discontinued as it may be removed in a future release. You should avoid becoming dependent on deprecated features and become familiar with the equivalent feature.

Release 3.4

The following feature is deprecated in the 3.4 release:

- `SELECT` event for Tree is deprecated and replaced with the `CHANGE` model event.

Deprecated APIs

The following APIs are deprecated in 3.4. For more information, see *TIBCO General Interface API Reference*.

Deprecated Classes

- `jsx3.xml.Processor` - use `jsx3.xml.Template`

Deprecated Fields

- `jsx3.app.Settings.DOMAIN_SYSTEM`
- `jsx3.gui.LayoutGrid.ABSOLUTE`
- `jsx3.gui.LayoutGrid.ADAPTIVE`
- `jsx3.gui.LayoutGrid.DEFAULTDIMENSIONS`
- `jsx3.gui.LayoutGrid.DEFAULTORIENTATION`
- `jsx3.gui.LayoutGrid.DEFAULTREPEAT`
- `jsx3.gui.LayoutGrid.ORIENTATIONCOL`
- `jsx3.gui.LayoutGrid.ORIENTATIONROW`
- `jsx3.gui.List.DEFAULTXSLURL`
- `jsx3.gui.Matrix.DEFAULT_INFO_LABEL` - value is now localized
- `jsx3.gui.Matrix.DEFAULT_XSL_URL` - renamed to `DEFAULTXSLURL`
- `jsx3.gui.Menu.DEFAULTXSLCACHEID`

- `jsx3.gui.Menu.NODATAMESSAGE`
- `jsx3.gui.Select.COMBOXSLID`
- `jsx3.gui.Select.COMBOXSLURL` - renamed to `DEFAULTXSLURL`
- `jsx3.gui.Select.SELECTXSLID`
- `jsx3.gui.Select.SELECTXSLURL` - renamed to `DEFAULTXSLURL`
- `jsx3.gui.StackGroup.DEFAULTDIMENSIONS`
- `jsx3.gui.StackGroup.DEFAULTSTACKCOUNT`
- `jsx3.gui.Tab.DEFAULTHIGHLIGHT`
- `jsx3.gui.Tab.DEFAULTSHADOW`
- `jsx3.gui.TextBox.OVERFLOWAUTO`
- `jsx3.gui.TextBox.OVERFLOWNORMAL`
- `jsx3.gui.TextBox.OVERFLOWSCROLL`
- `jsx3.gui.Tree.DEFAULTXSLID`
- `jsx3.gui.Tree.ONDROPBGIMAGE`
- `jsx3.xml.Cacheable.DEFAULTXSLCACHEID`

Deprecated Methods

- `jsx3.gui.LayoutGrid.getBestGuess()`
- `jsx3.gui.LayoutGrid.getDimensionArray()` - use `getRows()` and `getCols()`
- `jsx3.gui.LayoutGrid.getOrientation()` - use `getRows()` and `getCols()`
- `jsx3.gui.LayoutGrid.getRepeat()`
- `jsx3.gui.LayoutGrid.setBestGuess()`
- `jsx3.gui.LayoutGrid.setDimensionArray()` - use `getRows()` and `getCols()`
- `jsx3.gui.LayoutGrid.setOrientation()` - use `getRows()` and `getCols()`
- `jsx3.gui.LayoutGrid.setRepeat()`
- `jsx3.gui.Tree.getText()`
- `jsx3.net.Request.getReadyState()` - use the event publisher interface instead to track the state of the request.
- `jsx3.xml.Entity.getXML()` - use `toString()`

Release 3.2

The following features are deprecated in this release.

Deprecated APIs

The following APIs are deprecated in 3.2:

- The following `jsx3.xml.Cacheable` properties are deprecated:
 - XSL URL getters and setters
 - XSL ID getters and setters
 - XSL String getters and setters

Instead of these properties, use the XML transformers functionality: `getXMLTransformers()` and `setXMLTransformers()`.

- `jsx3.gui.insertHTML()` is replaced by `paintChild()`

Deprecated Prototypes

`Grid`, `List`, `Column`, and `MultiSelect` have been deprecated and moved to the **Deprecated** folder in the Component Libraries palette. `Matrix` and `Matrix Column` components replace `Grid`, `List`, and `Column`. See *Matrix Components* on page 19.

Release 3.1

The following features are deprecated in this release.

- **Class Structure** The class hierarchy has been completely reorganized in this release. This has resulted in the deprecation of many classes. Refer to the API documentation for the list of deprecated classes and their replacements.
- `jsx3.out` is replaced by `jsx3.log()` and class `jsx3.util.Logger`. For information on these features, see *General Interface Logging* at the TIBCO Developer Network web site at <http://developer.tibco.com>.
- **Event Model** Static access to the current event object (`jsx3.EVENT`) was deprecated. In addition, in order to support both the 3.0 and 3.1 model event protocols simultaneously, many methods have been either deprecated or made to branch based on which event protocol is in use. Methods have been deprecated or renamed when they existed solely to generate a model event or when their names implied that they generated a model event. Preexisting methods that have different behavior based on the model event protocol are considered branching methods. For more information, see *Model Events* on the TIBCO Developer Network web site at <http://developer.tibco.com>.

- **Various Methods and Fields** Consult the API documentation in General Interface Builder Help for other deprecated methods and fields. Deprecated members are indicated with a strike-through font.

Migration and Compatibility

To migrate projects from previous General Interface releases, see *TIBCO General Interface Migration* in the General Interface documentation.

Closed Issues

The tables in this section list issues that were closed in the named releases.

Charting

Closed in Release	Defect #	Summary
3.3.0	1-7XM18V	Any change to a chart's axis property that resulted in a negative computed value of the axis Left position ran the risk of generating -1INF (negative infinity) on Internet Explorer. This caused deserialization to fail.
3.1.1	1-6YXIXS	Events on chart series (and possibly other chart components) fired twice. The event handlers were incorrectly painted in the group containing the category shapes. They should have only been painted in the category shapes themselves.
3.1.0	1-5ZWDAG	When an empty area chart was created, an error was generated. This error occurred when there wasn't any data to display on chart axes.

Data Mapping Tools

Closed in Release	JIRA #	Defect #	Summary (Sheet 1 of 4)
3.4.0	GI-87	1-81TP0D	<p>The XML Mapping Utility was encoding soap messages that define a soap encoding style even if their 'use' was 'literal'. Instead, the XML Mapping Utility should only encode messages when both the encoding style is specified AND the 'use' is 'encoded'.</p> <p>Note: You can now edit the SOAP Use (encoded or literal) and the SOAP Encoding (http://schemas.xmlsoap.org/soap/encoding/) fields in the Rule Profile panel of the XML Mapping Utility. See XML Mapping Utility on page 3.</p>

Closed in Release	JIRA #	Defect #	Summary (Sheet 2 of 4)
3.4.0		1-80VDDB	<p>The XML Mapping Utility method, <code>getTargetedSchemaQuery()</code>, was improperly including schemas in its search scope. This problem occurred when a WSDL was parsed that:</p> <ul style="list-style-type: none"> included multiple schemas where a following schema had an import child that referenced the namespace for a previous schema
3.4.0		1-7TRW5X	<p>The Types drop-down list in the Mapping table didn't display when you clicked the drop-down arrow the first time. Also, the jsxnull ID displayed as the first item in the list instead of -Select- .</p>
3.4.0		1-7GUVAT	<p>Parsing a WSDL with SOAP version 1.2 using the XML Mapping Utility resulted in the following misleading error message:</p> <pre>[ERROR] The WSDL located at 'JSX/addins/mapping/samples/ldap-bw.wsdl' does not contain any soap bindings (i.e., '/wsdl:definitions/wsdl:service/wsdl:port/soap:ad dress'). Abstract WSDLs as well as protocols such as FTP and HTTP are not supported at this time.</pre> <p>Because the XML Mapping Utility doesn't support SOAP version 1.2, the error message was modified as follows:</p> <pre>The WSDL located at '{wsdl_url}' does not contain a valid reference to a supported version of SOAP. At this time only the following namespace(s) are supported: 'http://schemas.xmlsoap.org/wsdl/soap/' .</pre>
3.3.0		1-7X3AN7	<p>The <code>jsx3.net.Service</code> class was improperly sending the string value 'null' when a CDF attribute mapping was generating a value in the outgoing request. If the CDF attribute node was missing, no value should be set. If the CDF attribute node was an empty string, the value should be an empty string.</p>

Closed in Release	JIRA #	Defect #	Summary (Sheet 3 of 4)
3.3.0		1-7X3AFK	The <code>doCall()</code> method for the <code>jsx3.net.Service</code> class failed to include the XML prolog when sending request documents. This wasn't standard and could cause the request to be mishandled by the receiving server. The prolog should include <code><?xml version="1.0" ?></code> , should be sent with <code>doCall()</code> requests, and should also appear when using the Test Interface in the XML Mapping Utility (panel 2 in the Test Interface).
3.3.0		1-7VF6FY	When the XML Mapping Utility parsed an XML document (not a WSDL), the <code>xmlns</code> nodes in the pattern master were persisted as CXF rules. The <code>xmlns</code> nodes should have been ignored and not persisted as rules. This was incorrect and broke the service class when the given ruleset was run.
3.3.0		1-7C0PJX	Nodes were missing in the XML Mapping Utility. This occurred when a WSDL referenced a schema, which in turn referenced another schema. The XML Mapping Utility didn't support this feature and the behavior was as expected. The <code>xsd:extension</code> element won't properly parse if the element was based upon an <code>xsd:extension</code> element that was based upon yet another <code>xsd:extension</code> element.
3.3.0		1-7VF6D9	SOAP messages that didn't define a <code>soap:operation</code> node in the WSDL caused a null pointer exception in the XML Mapping Utility. The XML Mapping Utility needed to allow messages that didn't contain this node and continue parsing.
3.3.0		1-7VF6EC	When the XML Mapping Utility parsed a WSDL that contained a schema-defined node with the <code>nillable</code> attribute, the attribute wasn't honored. The <code>nillable</code> attribute, if explicitly declared, should have been added to the list of restrictions for the given node when it was first parsed by the XML Mapping Utility.
3.2.0		1-79SFGL	No alert occurred when the XML Mapping Utility tried to parse a mapping file that didn't exist. The error message reported that the type was unrecognized when it should have reported the file wasn't found.

Closed in Release	JIRA #	Defect #	Summary (Sheet 4 of 4)
3.2.0		1-768GLZ	Static service calls using <code>setInboundURL()</code> and <code>setOutboundURL()</code> don't work. For Inbound mappings to run, the HTTP status code must be 200, 202, or 0. This affected the <code>Service</code> class when running in test/static mode.
3.2.0		1-76D12H	Added support to the XML Mapping Utility to handle WSDLs created by BW 5.3.2.
3.2.0		1-72BKSN	The XML Mapping Utility didn't account for different namespaces when the element name was the same.
3.2.0		1-71UVED	The XML Mapping Utility ignored locally declared namespaces (those namespaces declared on a node), so it failed to see the data type for the part.
3.2.0		1-6Q2SLD	Used an asynchronous call for the XML Mapping Utility to keep the browser from locking up if the WSDL was unavailable. Provided a Cancel button so the user could cancel if the call was taking too long.
3.1.1		1-6Y3BDR	Mapping Rule Migration - The CXF Rule conversion utility didn't automatically set <code>Restriction = Nillable</code> for empty nodes present in 3.0 CXF Rules.
3.1.1		1-6XY6MN	XML documents remained in the IDE cache after rules creation and update, and then the XML Mapping Utility was closed. These XML documents accumulated each time the XML Mapping Utility was used and closed, taking up resources.
3.1.1		1-6XY6Q4	3.0 Rules with POST and empty message threw errors.
3.1.1		1-6XY6RN	When selecting a SOAP Fault node in the mapper, an unnecessary error message was sent to the General Interface Builder log.
3.1.0		1-63NS8X	The SOAP Mapping Utility (now renamed XML Mapping Utility) could lose the association to the rule being edited. When this happened, the Test Rules tab stopped functioning. This behavior had no impact on runtime behaviors or performance.

Deployment

Closed in Release	Defect #	Summary
3.2.0	1-772SE3	Select and Datepicker Heavyweight window were not anchored to the correct position when placed inside a dialog and deployed inside a portal page.

Documentation

Closed in Release	Defect #	Summary
3.4.0	1-7SPC40	When running in XHTML mode, API help threw an exception if the inline comments in the API documentation weren't XHTML-compliant. For example, API help for <code>jsx3.app.Server getEnv()</code> triggered an exception.
3.4.0	1-7Z3209	The <code>Matrix.Column</code> documentation was missing from API help (Help > API Documentation).
3.3.0	1-7TIWOV	The API documentation incorrectly stated that the <code>Matrix getSortPath()</code> and <code>setSortPath()</code> methods required the name of the attribute to be preceded by an @ symbol. The @ symbol wasn't required and would break the sort if it was used.

Firefox

Closed in Release	JIRA #	Defect #	Summary (Sheet 1 of 2)
3.4.0	GI-42	1-7ZPCAF	In Firefox 2 and 1.5, a long text string (wider than column width) in a select and select-combo mask column could run outside the drop-down box and onto the next column. If it was the last column of the matrix in a dialog, the long text could also run over the vertical scroll bar and out of the dialog.

Closed in Release	JIRA #	Defect #	Summary (Sheet 2 of 2)
3.4.0		1-7YR53C	In Firefox, the select-combo component was truncated to a width of 113 pixels regardless of the Width property setting.
3.4.0		1-7Y9ZKQ	In Firefox, if you right-clicked the Size Array field of a layout component in the Properties Editor palette and selected a custom-created dynamic property, the following error was displayed in the System Log: <pre>11:38:18.484 global (INFO) - (IDPR02) error evaluating expression 'objJSX.setDimensionArray(vntValue?vntValu e.split(/\s*[,;]\s*/):[],true)';': undefined at jsx3.ide#BJ() at jsx3.ide#p9() at jsx3#eval() at jsx3.lang.Object.eval() ...</pre>
3.2.0		1-77QPS3	When accessing data across multiple domains on Firefox 1.5.x in Windows and Mac, an exception was thrown. For example, this occurred when running the WSDL_Mapping_2 sample application. For Firefox, you must configure proxy communications. See <i>Configuring Proxy Communications</i> in the <i>Tips & Techniques</i> document, <i>Accessing Data Across Subdomains</i> , at http://developer.tibco.com .
3.2.0		1-7AP5XP	Moving the mouse over a context menu in Firefox may cause an error message in the System Log palette. This message can be ignored.

General Interface Builder

Closed in Release	JIRA #	Defect #	Summary (Sheet 1 of 4)
3.4.0		1-7YL8GT	In the Properties Editor palette, when you selected a property value from a drop-down menu, the same selection displayed for other properties with drop-down menus.

Closed in Release	JIRA #	Defect #	Summary (Sheet 2 of 4)
3.4.0	GI-34	1-7ZEQH0	The objEVENT context parameter in spyglass model events didn't have event information (<empty>).
3.4.0	GI-30	1-7ZW345	Although the Focus Rectangle was enabled in the Component Hierarchy palette, absolutely-positioned WindowBar instances couldn't be moved in the work area of the IDE.
3.4.0	GI-14	1-7WM1VJ	External files, such as xml, xls, and jss documents, that were set to auto-load=true weren't loaded into the application cache.
3.3.0		1-7WP11F	"Reset/Clear" in the Matrix.Column Format Handler property caused the following exception: 15:36:35.564 global (INFO) - (IDPR02)errorevaluating expression 'objJSX.setFormatHandler(vntValue);objJSX.repaint()': 'null' is null or not an object at jsx3.ide#BJ() at jsx3.ide#p9()
3.3.0		1-7WOXL9	When the children for a LayoutGrid were rearranged in General Interface Builder, the child blocks were not resized accordingly.
3.3.0		1-7UM83F	Add-in component icons weren't displayed correctly in the Component Libraries palette, because GI_Builder/ was prepended to the icon URI.
3.2.0		1-6BYOQP	jsx3.ide.debug() statements at runtime (or Project > Run) throw a JavaScript error in the browser. This is expected behavior. To prevent these errors, wrap debug statements in an if statement, which refers to a global isDebug variable. Then set the variable to True for development and False for deployment.
3.2.0		1-7A5UB3	The cursor was missing in the General Interface Builder editor when running in Firefox.
3.2.0		1-7CHI0R	When adding a new class path on the Classpath page of the Project Settings dialog (Project Settings > Classpath), an error was thrown and the new record didn't immediately display.

Closed in Release	JIRA #	Defect #	Summary (Sheet 3 of 4)
3.2.0		1-78QAO1	Unable to delete text area/textbox once it was dropped in the General Interface Builder work area toolbar (bottom of work area).
3.2.0		1-76FWL5	When switching projects in General Interface Builder after an exception, General Interface Builder appeared to be unresponsive. High CPU usage was observed (99%).
3.2.0		1-72UPUR	The method, <code>jsx3.net.Service getEndpointURL()</code> , appeared in API help but not when using the type-ahead feature (Ctrl+spacebar).
3.2.0		1-7AOYPQ	Restoring a Matrix Column from the Recycle Bin caused an exception.
3.2.0		1-6FEKS8	Certain sequences of author-time events, including toggling an object's properties between Absolute and Relative, could cause strange results later when trying to move the object by dragging the object's center point. The object appeared in a different location than where it was dropped.
3.2.0		1-6U3XMU	<code>jsx3.GO()</code> and other methods in getting a handle to an object which do not include the namespace found objects which have been placed in the trash can. This made updates to the view at author time unpredictable.
3.2.0		1-6X6AG4	When the Source XML (Expert) view of a GUI Component (2nd button on the bottom of the work area) was active, only the Project Files palette and the Local Data Cache palette should be enabled. Because other areas of the user interface were enabled, it was possible to make changes to the component using the Component Hierarchy palette or Properties Editor palette, and so on, which were not persisted.

Closed in Release	JIRA #	Defect #	Summary (Sheet 4 of 4)
3.2.0		1-6X6AIS	There was no warning given when a developer tries to import a Referenced or Referenced-async GUI component as a child of JSXBODY (the topmost node in the Component Hierarchy). All referenced components needed to be a child of an object in the component hierarchy of the referencing component. Otherwise, when the referencing component was saved, the reference was lost.
3.1.1		1-70Q8JU	The Properties Editor palette got out of alignment when the Enter key was used for navigation.
3.1.1		1-6Z6WKR	XML markup text didn't render in the logger.
3.1.1		1-6Z6C5E	<code>jsx3.app.Monitor</code> didn't escape HTML/XML markup text.
3.1.1		1-6ZS55H	Changing the Show Deprecated Classes option collapsed the tree, unselected the current class, and prevented the selection of methods.
3.1.1		1-6X6LLE	Pressing the Enter key while in the Type column of the Dynamic Properties Editor (or combo box column in any Grid) moved the focus two rows down.

General Interface Framework

Closed in Release	Defect #	Summary (Sheet 1 of 4)
3.4.0	1-7Z3211	<p>When a General Interface application was deployed to an HTTP server and the launch page for the application wasn't a sibling to the JSX directory, the following default system images were not resolved correctly:</p> <ul style="list-style-type: none"> The plus/minus toggling icon for tree and matrix-tree The transparent image used for all CDF controls The green check mark icon used for the select options list to denote which option is selected

Closed in Release	Defect #	Summary (Sheet 2 of 4)
3.3.0	1-7ZP9SH / 1-7YTIK0	<p>In some versions of Internet Explorer 6 and 7, XML, XSL, and JSS files were never cached by the browser. TIBCO General Interface has been modified to work around this issue.</p> <p>For more information on Internet Explorer caching and best practices, see "Understanding Internet Explorer Caching" at http://developer.tibco.com in the Tips and Techniques section.</p>
3.3.0	1-7XUQPP	The <code>jsx3.xml.Processor</code> constructor didn't accept <code>jsx3.xml.Entity</code> (and subclass <code>jsx3.xml.Document</code>) for the source document parameter.
3.3.0	1-7Y9EB1	The <code>jsx3.net.Form()</code> method caused an error due to obfuscation.
3.3.0	1-7U7YT1	The <code>activateOnHotKey</code> attribute of the application monitor (<code>logger.xml</code>) doesn't work. It should disable the application monitor until the hot key, <code>Ctrl+Alt+m</code> , is pressed in the application.
3.3.0	1-7WUUZU	The <code>jsx3.resolveURI()</code> method erroneously removed query parameters and fragment parts of the URI.
3.3.0	1-7VUMGR	In Internet Explorer and over HTTP, if a component file contained a dynamically loaded class and an include that referenced another component file that also contained the same dynamically loaded class, General Interface under certain conditions showed FATAL alerts about trying to reload the class.
3.3.0	1-7V4G99	The <code>jsx3.xml.Entity.setValue()</code> method caused inconsistent behavior in the XML Mapping Utility. In Firefox, this method was concatenating the string by appending each new bit of text, while in Internet Explorer it was replacing any existing text. The correct behavior was to replace all content of the entity with the text value of the input parameter, so that the only value of the entity is the newly added text value. Firefox and Internet Explorer now consistently handle the following methods: <code>setValue()</code> , <code>createNode()</code> , <code>insertBefore()</code> , and <code>appendChild()</code> .

Closed in Release	Defect #	Summary (Sheet 3 of 4)
3.3.0	1-7V4G9S	A Tabbed Pane container with two asynchronously loaded Matrix components (asynch referenced the same matrix) that were set with the Not Selectable property caused an exception: 18:02:38.747 global (ERROR) - Uncaught Exception: Reference to undeclared namespace prefix: 'xsl'.
3.2.0	1-7CIEMN	In General Interface Framework, there was a problem if you used an edit mask within a Matrix and that given Matrix instance didn't use any pagination (<code>jsx3.gui.Matrix.PAGING_OFF</code>). Calling the <code>redrawRecord()</code> method or any method that calls <code>redrawRecord()</code> , such as <code>insertRecord()</code> or <code>insertRecordNode()</code> , resulted in an error.
3.2.0	1-79I48Z	The Dynamic Properties editor (Matrix control) threw an exception when updating the <code>jsxid</code> column and required refresh to be in synch with underlying data.
3.2.0	1-73QTJ7	Removing a child of a layout grid (and its subclasses such as <code>StackGroup</code>) didn't properly remove the child HTML. This was true if the layout grid had been repainted but not true if the children had been added with <code>insertHTML()</code> .
3.2.0	1-72KUMP	Hot keys registered as properties of the button classes or registered as the <code>jsxkeycode</code> CDF attribute of menu should register themselves with the first ancestor DOM node that was a <code>jsx3.gui.Window</code> , <code>jsx3.gui.Dialog</code> , or root block of a server.
3.2.0	1-72G8V7	CDF records with only numeric IDs cause ID collisions.
3.2.0	1-70Q86W	Added missing <code>getServer()</code> method to the <code>jsx3.net.Service</code> class, allowing for more consistent experience in both General Interface Builder and runtime.
3.2.0	1-712JG1	It wasn't possible to combine nodes or documents that were created using differing threading models. The threading model used by the <code>xmlhttp</code> control and the threading model used by static XML documents were different.
3.2.0	1-6X3V2V	Adding more than two children to a splitter parent caused unpredictable runtime behavior.

Closed in Release	Defect #	Summary (Sheet 4 of 4)
3.1.1	1-72252X	<code>jsx3.net.Service.setTimeout</code> caused JavaScript error, "onTimeout is undefined".
3.1.1	1-6XP1CC	XSL document was reloaded when destroying List/Grid.
3.1.1	1-6YKVJL	<code>Date Picker</code> failed in GMT- <i>nn</i> time zones.
3.1.0	1-692LVH	The JavaScript function <code>setTimeout</code> was not supported in the version of the HTTP object referenced in Project Deployment Options.

GUI Components

Closed in Release	JIRA #	Defect #	Summary (Sheet 1 of 8)
3.4.0	GI-103	1-84ZLB9	The <code>@lookup</code> format handler didn't resolve lookups unless the edit mask was a direct child of the matrix column. Therefore, matrix column <code>@lookup</code> format handler didn't work with <code>BlockMask</code> or a <code>DialogMask</code> .
3.4.0	GI-102	1-84ZL9Z	Applying focus to a cell that was non-existent because it belonged to a paginated matrix didn't work. If the cell didn't exist, the Matrix should be scrolled to the correct location, so that the given page that contained the cell was rendered and the cell was made available for focus. In addition, there wasn't a method, <code>revealRecord()</code> , as is provided by <code>tree</code> , meaning it wasn't possible to display a given cell without first applying focus.
3.4.0	GI-101	1-84ZL8Z	The <code>setValue()</code> method wasn't properly implemented by the matrix. When passing an ID or an array of IDs if selection model is multi-row, the given record(s) weren't selected and the first record wasn't scrolled into view.
3.4.0	GI-100	1-84TGPY	Drag-and-drop from <code>Tree</code> to <code>Matrix</code> didn't work. Also, poor support for adoption of records that contained nested records.

Closed in Release	JIRA #	Defect #	Summary (Sheet 2 of 8)
3.4.0	GI-96	1-8434XJ	Matrix with paging off should apply format handlers synchronously at <code>repaint()</code> and <code>repaintData()</code> . This will eliminate flickering in this case.
3.4.0		1-834YTH	Dialog when dragged didn't have top-most Z-index, so that it appeared to drag behind other dialogs.
3.4.0	GI-97	1-843RIP	Heavyweight windows, such as menu and select drop-down list, didn't move with the menu anchor or select box when the browser window was resized. This was especially apparent when a block container was right-aligned.
3.4.0	GI-95	1-842SW4	KEYUP event didn't fire for combo select.
3.4.0	GI-84	1-83WMBP	Form elements didn't inherit font color from the ancestor block.
3.4.0	GI-91	1-834QR3	Setting the Tag Name property of block in General Interface Builder didn't regenerate the HTML.
3.4.0	GI-90	1-830NQL	In the Properties Editor palette in General Interface Builder, switching the Type property from textbox to textarea or textarea to textbox didn't work.
3.4.0	GI-88	1-82I3L9	Saving an XML file in General Interface Builder with an XML declaration created "unsupported" comment.
3.4.0	GI-38	1-818IT6	The <code>objEVENT</code> was null in the CHANGE model event context of <code>jsx3.gui.Slider</code> when using the up and down arrow keys to edit values.
3.4.0	GI-37	1-81B3K3	The Time Picker didn't respond to the number pad of the keyboard.
3.4.0	GI-85	1-81HAI7	The <code>jsx3.gui.Button.focus()</code> method didn't apply focus to the correct HTML DOM node and didn't work at all in Firefox.
3.4.0	GI-86	1-81HOEW	If a dialog with a select-combo component was moved on the screen, it lost its value and new values couldn't be assigned even though they could be selected from the drop-down list.

Closed in Release	JIRA #	Defect #	Summary (Sheet 3 of 8)
3.4.0		1-80I857	When the No Wrap property was set for a text area, text was still wrapped.
3.4.0	GI-43	1-80OOH3	When deserialized a dialog box top-left position could be at a negative position if the min-width and min-height were larger than the client window and no top-left positions were defined. Call <code>constrainPosition(true)</code> if there is a chance that the dialog is larger than its parent.
3.4.0	GI-12	1-7Y9ZJR	The Font Weight property for the toolbar button wasn't working properly.
3.4.0		1-7GFNGT	If a drop-down menu had a vertical scroll bar, it might have been impossible to move the mouse to a submenu without hiding the submenu. In Internet Explorer, mousing over the scroll bar caused a mouse out event on the active menu item.
3.4.0		1-7DS71V	The main body of the Matrix didn't respond to the scroll wheel on the mouse.
3.4.0	GI-33	1-7ZOVRR	Matrix didn't conform to the contract of <code>jsx3.gui.Form</code> , because it didn't implement <code>doValidate</code> . Note that <code>doValidate()</code> returns 1 if the form element is optional or if it's required and at least one row is selected.
3.4.0	GI-22	1-7YR59D	Entering text in the Text/HTML property of a block in the Properties Editor palette and adding a select component to the same block, prevented the General Interface Builder tabs from working and you couldn't switch between tabs.
3.4.0	GI-21	1-7YTKVZ	The tab EXECUTE event didn't fire when the tab was clicked.
3.4.0	GI-8	1-7C7LIW	The Text field in the combo component wasn't disabled when the component was flagged as "disabled."
3.4.0		1-7YTJ72	If a dialog that contained a Matrix Grid was moved while a text edit box in the grid had focus, the text box couldn't receive focus or be edited after it was moved.

Closed in Release	JIRA #	Defect #	Summary (Sheet 4 of 8)
3.4.0		1-7KV0SU	<p>Tabs don't cascade to the next row if they exceed the viewable space.</p> <p>TabbedPane now provides an automatic right and left scrolling mechanism for navigating through tabs that are hidden when they exceed the viewable space. Hover over the right or left arrow icons to scroll through the hidden tabs. You can also navigate tabs using the right and left arrow keys.</p>
3.4.0	GI-63	1-6THXVP	<p>Submenus and menus weren't aware enough to always cascade in the most optimal direction. Long menus at the bottom of the screen, particularly those with long submenus, were rendered with scroll bars. Long menus now render with auto-scroll arrows instead of scroll bars.</p>
3.3.0		1-7XUQQU	<p>Calling the <code>dialog.focus()</code> method on a modal dialog caused the loss of modal.</p>
3.3.0		1-7Y9EC9	<p>Some formats of the <code>jsx3.gui.Matrix.ColumnFormat.getInstance()</code> method didn't work.</p>
3.3.0		1-7XJ0NF	<p>Several XSLT features (particular as implemented by the Matrix) caused a noticeable slowdown. First, due to browsers not caching XSL imports, any repaint command on a Matrix (or the other CDF controls) forced a roundtrip to the server, which caused a substantial impact on even the smallest update. In addition, the Matrix should expose a public API that allows developers direct access to the native HTML element for a Matrix cell. This was critical when integrating with technologies, such as Comet, DWR, or Lightstreamer, where using XSLT for a simple update to a cell was CPU intensive.</p> <p>Added a new public method to Matrix, <code>getContentElement()</code>, that allows access to the HTML element by providing the CDF record id and the named attribute on the CDF.</p>

Closed in Release	JIRA #	Defect #	Summary (Sheet 5 of 8)
3.3.0		1-7X9FEW	Importing failed with an exception when canvas was "dirty" (after adding a new container and trying to import into its pane).
3.3.0		1-7X3RV2	The cursor for Matrix cells in Internet Explorer appeared as the text cursor (cursor:text;) except in portions of header cells where text wasn't present.
3.3.0		1-7X3RSF	In Internet Explorer, unless a row in the Matrix explicitly implemented a bgcolor (specified in the XSL Parameters Palette or the Properties Editor palette), the text bled through onto the next cell in the row.
3.3.0		1-7X3APA	The <code>jsx3.gui.Button</code> class couldn't be toggled from relative to absolute and have the left/top be honored.
3.3.0		1-7WS633	With a Matrix row selected, switching the application focus to another application, such as Notepad, and then switching back to the browser caused multiple (2) select events to be triggered.
3.3.0		1-7WS62L	After resizing the Properties Editor palette and the Events Editor palette by resizing the splitter pane or resizing the browser window, "Reset/Clear" a property caused the name cell to expand in size.
3.3.0		1-7U5AVZ	The Space key didn't trigger select (or execute) event for a Matrix List or a Matrix Grid.
3.3.0		1-7T8Y2X	A Dialog could be resized to a "floating" drag corner image by dragging the left bottom edge of the dialog to the right top edge.
3.3.0		1-7TLD4E and 1-7UM7XG	When a Tree was already displayed on the screen and the <code>insertRecord()</code> method was used to add the first new child record to a node, the new Tree node displayed was detached from the parent node.

Closed in Release	JIRA #	Defect #	Summary (Sheet 6 of 8)
3.3.0		1-7VK76Z	In Internet Explorer 6, a modal dialog invoked from a menu in a layout pane wasn't rendered correctly. This occurred on initial loading of dialog and every other loading of dialog, such as third and fifth. On the second, fourth, and sixth loading of dialog, the modal dialog was rendered correctly.
3.2.0		1-6RBJ3S	Keyboard navigation couldn't be used with the Date Picker component, which obstructed the process of using the Tab key to select components.
3.2.0		1-6OUN7V	<code>jsx3.gui.List/Grid</code> - Unselectable nodes in List/Grid could trap focus, blocking keyboard navigation past those items.
3.2.0		1-7RUQNG	While dragging a record from a can drag Matrix control to another drop-enabled Matrix control, the mouse cursor is changed into a forbidden cursor (/).
3.2.0		1-7D33L9	Calling the <code>setDisplay()</code> method on a Matrix Column child should result in the XSLT for the owning Matrix to be reset.
3.2.0		1-7CM78U	When using a paginated instance of the Matrix (<code>jsx3.gui.Matrix.PAGING_PAGED</code>), if records were added and removed and the Matrix was then repainted (by calling <code>repaintData()</code> or <code>repaint()</code>), the scroll bars didn't update to reflect the changed record count.
3.2.0		1-78Q4ZV	Selecting a Matrix cell on the right-hand side of the grid caused the grid to jump to the left.
3.2.0		1-7AMECV	Selecting a different node in the Component Hierarchy palette while editing a property in the Properties Editor palette might have caused the change to affect the newly selected object, not the intended object.
3.2.0		1-79KHWA	Using the Tab key in the Properties Editor palette after editing a value triggered an exception. The Tab key didn't work in the Matrix component.
3.2.0		1-785LPA	Stack gradient color disappeared after mouse over, then mouse out.

Closed in Release	JIRA #	Defect #	Summary (Sheet 7 of 8)
3.2.0		1-785LOQ	Stack () layout had text displayed horizontally instead of vertically.
3.2.0		1-77QQDH	Splitter handle custom image could fail in distributed deployments.
3.2.0		1-75ZTPK	Menus bound to lists didn't always work properly, because the Object ID argument was missing from <code>jsx3.gui.Menu setMenu()</code> .
3.2.0		1-74NKH7 and 1-75ZTO1	In CDF data, images in <code>tree/menu/list/grid</code> that refer to <code>JSX/images</code> or <code>JSXAPPS/application_dir/images</code> didn't resolve correctly when the <code>JSX</code> directory and <code>JSXAPPS/application_dir</code> directory didn't reside in the same directory as the launching HTML page.
3.2.0		1-748XL9	Dialog failed to paint content after being maximized if it was window-shaded.
3.2.0		1-70ZZYW	Missing a method to unselect a selected item in Grid. There wasn't a functional equivalent to List behavior.
3.2.0		1-6A9E3T	<code>jsx3.gui.Tree</code> — Key navigation in a tree followed the order of the records in the underlying CDF document. If the View was resorted using the XSL parameter <code>jsxsortpath</code> , arrow key navigation in the tree wouldn't follow the order of onscreen tree nodes, resulting in unexpected behavior.
3.2.0		1-6OJO49	<code>jsx3.gui.Tree</code> - Trees with hidden root nodes took a long time to paint when they were enclosed several levels deep within other components, and the ancestor components were repainted. Setting the Show Root Node property to <code>Hide</code> caused 15 second repaint. Setting to <code>Show</code> , resulted in instant repaint.
3.2.0		1-6XUR3U	Pressing Tab or Shift+Tab while in an open select or combo box should select the current item, close the select/combo, and move focus to the next (previous) item.

Closed in Release	JIRA #	Defect #	Summary (Sheet 8 of 8)
3.2.0		1-6VWJ99	<code>jsx3.gui.Grid</code> — Grid won't accept a drop unless the auto-expand property was set to TRUE. This resulted in an on-screen control that added extra rows to the view each time the user clicked in the last row of the Grid.
3.2.0		1-3HVT9B	The Properties Editor palette was missing a no border property.
3.1.1		1-70Q8IS	Combo control for grid failed to check for 'null' on the 'select' event, causing quirky behavior.
3.1.1		1-6XJTCH	Dialogs — Clicking a Dialog icon in the taskbar should bring the dialog forward if it wasn't forward. Instead, it minimized the dialog. The requested behavior follows that of Windows taskbar and Windows icons.
3.1.1		1-6X98XH	Alerts with large text blocks didn't scroll and the OK button disappeared.
3.1.1		1-6WT94Q	The Radio button prototype column didn't have a default groupname, so the radio button column didn't work as expected.

Installation and Build

Closed in Release	Defect #	Summary
3.1.1	1-6ZL8JH	When overwriting an existing installation, the Installer permanently deleted user-created files (files which were not installed as part of the package).

Samples

Closed in Release	Defect #	Summary
3.4.0	1-8494E7	Because Xignite now requires registration for access to the service, the WSDL_Mapping_2 sample has been modified to run in Static mode. To receive live data, you must register with Xignite and modify the sample to run in Live mode.

Known Issues

This section discusses known issues in this release.

Browser Limitations and the Margin Property

The behavior of the margin property varies by browser as follows:

- Internet Explorer applies all margins properly when the object is rendered, but if an ancestor container is ever hidden (`display:none`), the left margin is no longer honored when redisplayed.
- Firefox applies all margins if the object does not specify an overflow property (`overflow:hidden`, `overflow:auto`, `overflow:scroll`). If the object uses overflow, the top and bottom margin settings aren't honored.

In summary, margin properties are honored as follows:

- The only margin setting that is honored by all browsers in all situations is `margin-right`.
- The margin properties, `margin-top`, `margin-bottom`, and `margin-right`, are honored in all browsers if the object does not specify an overflow property of `hidden`, `scroll`, or `auto`.
- The margin properties, `margin-top`, `margin-bottom`, `margin-left` and `margin-right`, are honored in all browsers if the object does not specify an overflow property (`hidden`, `scroll`, or `auto`) and no ancestor of the object ever has its `display` property toggled between `none` and `block`.

Data Mapping Tools

Defect #	Summary/Workaround
1-7YL8IO	<p>Summary In Internet Explorer 7 with MSXML 3.0, when you select a complex parent type in the Rules tree of the XML Mapping Utility and choose Map > DOM (Map and Create), the menu command fails.</p> <p>Workaround Select a child or children of the complex parent type and choose Map > DOM (Map and Create).</p>

Defect #	Summary/Workaround (Cont'd)
1-70DGBK	<p>Summary While retrieving and parsing a remote WSDL document in the XML Mapping Utility, if the developer makes a typo in the URL, General Interface Builder locks up until the server returns a "document not found" error.</p> <p>Workaround Do not make typos in the URL field or work from a local copy of the WSDL.</p>

Documentation

Defect #	Summary/Workaround
1-7T8VF1	<p>Summary Not all classes that extend Block implement all of the methods or input types available to Block. In these cases, the API documentation lists those methods. The Properties Editor palette accepts and displays only the correct members.</p>

Firefox

JIRA #	Defect #	Summary/Workaround (Sheet 1 of 2)
GI-89	1-82IIVT	<p>Summary General Interface does not currently support the use of <code>document.domain</code> for applications running under Firefox. This is due to Mozilla bug 326337 "XMLHttpRequest.responseXML permission denied if document.domain set."</p> <p>When <code>document.domain</code> is called in Firefox, <code>XMLDocument</code> object returned by <code>XMLHttpRequest</code> or <code>document.implementation.createDocument</code> throw permission denied exceptions when any of its attributes and methods are accessed. This is a Firefox defect.</p>
	1-83YTXT	<p>Summary On Firefox, if a textbox is a child of a relatively positioned Block with absolute size (W:200,H:200), the textbox takes on the height of the Block container even though it specifies a different height (W:100,H:30).</p>
GI-92	1-834QRK	<p>Summary On Firefox, when a matrix in a dialog is minimized and restored, the scroll bar resets to the top, but the matrix rows aren't reset to the top row.</p>

JIRA #	Defect #	Summary/Workaround (Sheet 2 of 2)
	1-78I4SR	Summary On a Mac, text in charts on Firefox 1.5.x doesn't display properly. The text is drawn correctly but after dragging the parent, it isn't redrawn. In some cases, text is drawn when the scroll bar is scrolled. This defect has been reported to https://bugzilla.mozilla.org/show_bug.cgi?id=316564 .
	1-7T87PZ	Summary On Firefox, when you drop a charting component onto the work area and try to shift focus to that component using the Show/Hide Focus Rectangle button, the charting component doesn't receive the focus. Therefore, you can't drag and drop the component as desired. This defect has been reported to https://bugzilla.mozilla.org/show_bug.cgi?id=360141 .
	1-74L8YJ	Summary General Interface Builder error sound does not play properly in Firefox 1.5.x. Workaround Download and install a plug-in for .wav files.
	1-7A9DSG	Summary Firefox can't open non-XML files encoded as UTF-16. Workaround Use the General Interface Builder IDE, Internet Explorer, or a text editor to convert to 8-bit encoding before opening in Firefox.

Mac and Firefox Known Issues

Mac OS X and Firefox have the following known issues.

- The JavaScript Step Through Debugger isn't supported in Firefox. To debug in Firefox, use the Venkman extension at <http://getahead.ltd.uk/dwr/ajax/venkman/>.
- Inconsistent scroll bar support on Mac OS X. Also if layering is used, such as a dialog layered over an application, scroll bars bleed through. This occurs whenever z-index is used. See defect 1-7SGRHB on page 63.
- For charting on Firefox with Mac OS X, some SVG behavior is unexpected. For example, text isn't always rendered properly due to clipping. This is possibly related to scrolling. See defect 1-78I4SR on page 59.
- Mac OS X accelerator keys don't always work in Firefox.
- Firefox doesn't support `jsx3.net` .Form with file upload. As an alternative, set the Text/HTML property of a Block component to free form HTML containing a form element.
- Unexpected layout behavior in Firefox with the Block component, such as misaligned GUI components, when using relative positioning.

Workaround To avoid unexpected layout behavior in deployed applications, it's recommended to use Block as a container **only** if it meets **one** of these requirements:

- The Block is owned by a layout manager, such as LayoutGrid, Tab, Stack, and Splitter.
- The Block is relatively positioned and has a width of 100%.
- The Block is absolutely positioned.
- Overflow on a draggable object, such as a dialog, is hidden.

Workaround Make the dialog visible by adding width and height.

- XPath/XSLT in Firefox

- The XSL must meet these requirements in Firefox or it fails:

The XSL must point to the following namespace:

```
xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
```

The XSL must output valid XML. Balanced tags are required. For example,
`<xMessage>Hello World!</xMessage>`

- XSLT implementation does not support the namespace axis, limiting the ability to query and discover namespaces. The DOM-based interface also fails to implement this axis.
- XSLT implementation does not support the `node-set()` method, which means that complex parameters and result tree fragments cannot be resolved.
- XSLT implementation does not allow output escaping to be disabled, which means that escaped entities cannot be resolved during a transformation.

The only output formats supported for XSLT processing are HTML 4.0 and XML.

General Interface Builder

Defect #	Summary/Workaround (Sheet 1 of 3)
1-852K7J	<p>Summary Internet Explorer external add-ons, such as Yahoo and Developer toolbars, might interfere with opening the API documentation in a separate window (Help > API Documentation > Open in separate window) and trigger multiple blank pages in Internet Explorer 6 and Internet Explorer 7.</p>
	<p>Workaround Open the API documentation in a dialog or in the HTML version or disable external add-ons before opening in a separate window.</p>

Defect #	Summary/Workaround (Sheet 2 of 3)
1-84SURZ	<p>Summary In Internet Explorer 7, you can't open General Interface Builder in XHTML mode (<code>GI_Builder.xhtml</code>) even though the <code>xhtml</code> extension is configured to be opened by Internet Explorer 7. If you attempt to open General Interface Builder in XHTML mode, the Open/Save/Cancel dialog displays.</p> <p>Workaround Rename the file to <code>GI_Builder.xhtml.html</code> to open with Internet Explorer 7.</p>
1-7T33C9	<p>Summary On Mac, menu accelerator hot keys aren't working for some General Interface Builder menu items. For example, IDE Settings (<code>Ctrl+,</code>), Project Settings (<code>Ctrl+Shift+,</code>), and all palettes (<code>Ctrl+1</code>, <code>Ctrl+2</code>, and so on). This defect has been reported to https://bugzilla.mozilla.org/show_bug.cgi?id=106048.</p>
1-7QJTEX	<p>Summary In Internet Explorer, you can't create a new folder under the <code>C:\</code> root directory using the Create New Folder button while creating a workspace folder. Creating subfolders under an existing folder is not an issue.</p> <p>Workaround Create the folder under the <code>C:\</code> root directory in the Windows file manager. In General Interface Builder, choose the Browse button in the Create or Locate a Workspace dialog or in the Workspace field of the IDE Settings dialog (Tools > IDE Settings > Paths) and select the newly created folder.</p>
1-7HWJMF	<p>Summary When running General Interface Builder in Internet Explorer, the following steps cause an exception:</p> <ol style="list-style-type: none"> 1. The browser does not occupy the entire screen. 2. The Properties Editor palette is docked on the right side. 3. A property in the Properties Editor palette is being edited that uses a textbox mask. 4. The developer selects the text and continues the selection off the right edge of the browser. 5. The developer releases the mouse off the right edge of the browser. <p>Workaround Avoid the previously listed steps.</p>
1-79MFUX	<p>Summary Firefox determines the user home from the install directory and is case-sensitive, even though the file system is case-insensitive.</p> <p>Workaround If you change the browser URL from <code>C:</code> to <code>c:</code>, you need to specify the user home directory again.</p>

Defect #	Summary/Workaround (Sheet 3 of 3)
1-6E1BI5	<p>Summary When working in editable text tabs (JavaScript, XML, XSL, etc.) in General Interface Builder, the type-ahead context menu (activated with Ctrl+spacebar) becomes disabled under certain circumstances.</p> <p>Workaround Click anywhere in the edit window to reset the Ctrl+spacebar listener.</p>
1-6VYSPR	<p>Summary When General Interface Builder is launched from the HTA file, if Windows XPSP2 goes to sleep, Internet Explorer hangs when the user re-logs into Windows.</p> <p>Workaround Launch General Interface Builder from GI_Builder.html.</p>
1-6Y33HD	<p>Summary The Debugger occasionally evaluates a commented line.</p>

General Interface Framework

Defect #	Summary/Workaround
1-7T5QGX	<p>Summary Matrix controls created in the General Interface 3.2 Beta 2 release cause “no such method” or “function required” exceptions when loaded with General Interface 3.2. This is due to obfuscated variants in the serialization files.</p> <p>Workaround Check the serialization file for obfuscated variant attributes, such as <code>hk=" []"</code>. Remove these obfuscated variants manually in Source XML (Expert) view in General Interface Builder or use a text edit tool to search and remove all instances.</p>

GUI Components

JIRA #	Defect #	Summary/Workaround (Sheet 1 of 2)
	1-859IQ7	<p>Summary In XHTML mode, an error is thrown when a value is entered in the IFrame Source URL field in the Properties Editor palette. The error is also thrown when selecting Reset/Clear from the context menu:</p> <pre>15:27:18.623 global (INFO) - (IDPR02) error evaluating expression 'objJSX.setSrc(vntValue);': undefined at jsx3.ide#Ti() at jsx3.ide#on() at jsx3#eval() at anonymous(e, b) { return jsx3.eval.call(this, e, b); } at jsx3.gui.Interactive.doEvent() at jsx3.gui.Matrix.K8() at jsx3.gui.Matrix.HI() at jsx3.gui.Matrix.CH() at jsx3.gui.Interactive.Vi() at onFocus(event) { jsx3.GO("_jsx_0_2b").Vi(event, this, "CH"); } at focus() { [native code] } at anonymous() { try { c.focus(); } catch (Kc) { } } at jsx3#xC()</pre> <p>Workaround Use HTML mode instead of XHTML mode to enter and clear the Source URL field.</p>
GI-99	1-84QDH6	<p>Summary In Internet Explorer 7 XHTML mode, menus aren't rendered correctly. For example, submenus are detached and can't be selected.</p> <p>Workaround Run in HTML mode instead of XHTML mode.</p>
GI-93	1-834QYZ	<p>Summary When the select/option drop-down list is long, the vertical scroll bar takes up space within the drop-down window instead of getting extra width and the longer select text is truncated.</p>
	1-7SGRHB	<p>Summary On Mac OS X, if multiple dialogs are open, the vertical scroll bars of the bottom dialog bleed through to the dialog on top. This defect has been reported to https://bugzilla.mozilla.org/show_bug.cgi?id=187435.</p>

JIRA #	Defect #	Summary/Workaround (Sheet 2 of 2)
1-7XR6J9 and 1-7BPVY0		<p>Summary In a multiple-level menu, moving the mouse quickly in and out of a nested submenu causes the submenu to detach and move to the top left of the browser window. The problem is most apparent when the submenu is long or when the browser is repeatedly refreshed. The following exception is thrown:</p> <pre>12:54:06.826 global (ERROR) - Uncaught Exception: 'p.Te[...] ' is null or not an object (line: 0, file: file:///C:\Tibco\tibco-gi-3.3-pro\GI_Builder.html) at jsx3.gui.Menu#_u() at jsx3.gui.Menu.xo() at anonymous() { if(N.getParent()==null)return;p.Ps=null;p.FD=null;N.x o(n+1, true);} </pre> <p>Workaround Move the mouse more slowly.</p>
1-6Y5QMD		<p>Summary Trees which contain more than 15-20 nested levels do not render completely in the browser. Although the HTML is painted by the General Interface Framework, the browser does not render all the levels.</p> <p>Workaround Use the Matrix components.</p>
1-754023		<p>Summary Cursor in text tabs bleeds through a dialog in front of it.</p>